


Super Fast Soft Recovery Rectifier

Features

- Miniature axial leaded
- Glass passivated
- Hermetically sealed glass envelope
- Low reverse current



95 10526

Applications

High frequency circuits
 Freewheeling diodes in SMPS

Absolute Maximum Ratings

 $T_j = 25^\circ\text{C}$

| Parameter | Test Conditions | Type | Symbol | Value | Unit |
|---|--|--------|---------------------|------------|------------------|
| Reverse voltage =Repetitive peak reverse voltage | | BYT44A | V_R $=V_{RRM}$ | 50 | V |
| | | BYT44B | | 100 | V |
| | | BYT44C | | 150 | V |
| | | BYT44D | | 200 | V |
| Peak forward surge current | $t_p=8.3$ ms, half sinewave | | I_{FSM} | 30 | A |
| Average forward current | Lead length $l = 10$ mm, $T_L = 25^\circ\text{C}$ | | I_{FAV} | 1.5 | A |
| Junction and storage temperature range | | | $T_j=T_{stg}$ | -55...+175 | $^\circ\text{C}$ |

Maximum Thermal Resistance

 $T_j = 25^\circ\text{C}$


| Parameter | Test Conditions | Symbol | Value | Unit |
|------------------|--|------------|-------|------|
| Junction ambient | Lead length $l = 10$ mm, $T_L = \text{constant}$ | R_{thJA} | 60 | K/W |
| | on PC board with spacing 25mm | R_{thJA} | 110 | K/W |

Electrical Characteristics


 $T_j = 25^\circ\text{C}$

| Parameter | Test Conditions | Type | Symbol | Min | Typ | Max | Unit |
|---------------------------|--|--------|-------------|-----|-----|-----|---------------|
| Forward voltage | $I_F = 1\text{A}$ | | V_F | | | 1.1 | V |
| Reverse current | $V_R = V_{RRM}$ | | I_R | | | 5 | μA |
| | $V_R = V_{RRM}$, $T_j = 150^\circ\text{C}$ | | I_R | | | 150 | μA |
| Reverse breakdown voltage | $I_R = 100\mu\text{A}$ | BYT44A | $V_{(BR)R}$ | 50 | | | V |
| | | BYT44B | $V_{(BR)R}$ | 100 | | | V |
| | | BYT44C | $V_{(BR)R}$ | 150 | | | V |
| | | BYT44D | $V_{(BR)R}$ | 200 | | | V |
| Reverse recovery time | $I_F = 0.5\text{A}$, $I_R = 1\text{A}$, $i_R = 0.25\text{A}$ | | t_{rr} | | | 25 | ns |


Characteristics ($T_j = 25^\circ\text{C}$ unless otherwise specified)




96 12151 R_{thJA} – Therm. Resist. Junction / Ambient (K/W)
 l – Lead Length (mm)
 Figure 1. Max. Thermal Resistance vs. Lead Length




96 12150 I_R – Reverse Current (μA)
 T_j – Junction Temperature ($^\circ\text{C}$)
 Figure 4. Max. Reverse Current vs. Junction Temperature



96 12148 I_{FAV} – Average Forward Current (A)
 T_{amb} – Ambient Temperature ($^\circ\text{C}$)
 Figure 2. Max. Average Forward Current vs. Ambient Temperature




96 12147 I_F – Forward Current (A)
 V_F – Forward Voltage (V)
 Figure 5. Max. Forward Current vs. Forward Voltage



96 12149 I_{FAV} – Average Forward Current (A)
 T_{amb} – Ambient Temperature ($^\circ\text{C}$)
 Figure 3. Max. Average Forward Current vs. Ambient Temperature

Dimensions in mm

Standard Glass Case
DOT 30 B
Weight max. 0.5g



Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems
with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay-Telefunken products for any unintended or unauthorized application, the buyer shall indemnify Vishay-Telefunken against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423