

**Features**

- Output voltage 2.5/2.7/2.8/3.0/3.3/4.5/5.0V
- Output current 150mA
- Output noise voltage  $35 \mu V_{rms}$  typ.
- No-load input current  $90 \mu A$  typ.
- I/O voltage difference 0.1V typ.( $I_o=50mA$ )
- Ripple rejection ratio 70dB typ.
- Built-in On/Off control


**General Description**

The AT1201 is a low-noise, low-dropout, low-quiescent-current linear regulator designed for battery-powered applications. The output voltage precision is within  $\pm 2\%$  and output currents of up to 150mA ; the input/output voltage difference at 50mA is only 0.1V.

**Applications**


- Cordless phones
- Portable phones, PHS
- Other battery operating system

**Block Diagram**



**Aimtron reserves the right without notice to change this circuitry and specifications.**

### Pin Assignment



### Ordering Information

Part number	Package	Marking
AT1201-□□X	SOT-25	▲▲▲▲▲ Date Code
AT1201-□□X_Green	SOT-25, Green	▲▲▲▲▲, Date Code with one bottom line
AT1201-□□XR	SOT-25	▲▲▲▲▲ Date Code
AT1201-□□XR_Green	SOT-25, Green	▲▲▲▲▲, Date Code with one bottom line

□□: Output Voltage 25::2.5V 27::2.7V 28:2.8V 30:3.0V 33:3.3V 45::4.5V 50:5.0V

■: A:5V B:3.3V C:3.0V D:2.8V E:2.7V F:4.5V G:2.5V

▲▲▲▲▲: Date Code

\*For more marking information, contact our sales representative directly

### Absolute Maximum Ratings

Item	Symbol	Ratings	Units
Storage temperature	T <sub>STG</sub>	-40 ~ +125	°C
Operating temperature	T <sub>OPR</sub>	-30 ~ +85	°C
Power supply voltage	V <sub>CC</sub>	-0.3 ~ +14	V
Output current	I <sub>OUT</sub>	200	mA
Power consumption	P <sub>d</sub>	150	mW


### Recommended Operating Condition

Item	Symbol	Ratings	Units
Operating temperature	T <sub>OP</sub>	-20 ~ +75	°C
Output current	I <sub>OP</sub>	0 ~ 150	mA
Operating voltage	V <sub>OP</sub>	3.4 ~ 10	V

**Electrical Characteristics** (Except where noted otherwise,  $T_a = 25^\circ\text{C}$ )


Item	Symbol	Measurement conditions	Min.	Typ.	Max.	Units
Output voltage	$V_O$	$V_{IN} = V_O + 1\text{V}$ , $I_O = 30\text{mA}$	$V_{OUT} - 2\%$	$V_{OUT}$	$V_{OUT} + 2\%$	V
No-load consumption current	$I_{ccq1}$	$V_{IN} = V_O + 1\text{V}$ , $I_O = 0\text{mA}$		90	180	$\mu\text{A}$
Input current while off	$I_{ccq2}$	$V_{IN} = V_O + 1\text{V}$ , $V_{CONT} = 0\text{V}$			0.1	$\mu\text{A}$
I/O voltage difference	$V_d \text{ min}$	$V_{IN} = V_O - 0.2\text{V}$ , $I_O = 50\text{mA}$		0.1	0.2	V
Input fluctuations	$\Delta V1$	$V_{IN} = V_O + 1\text{V} \sim 10\text{V}$ , $I_O = 50\text{mA}$		10	20	mV
Load fluctuation	$\Delta V2$	$V_{IN} = V_O + 1\text{V}$ , $I_O = 0 \sim 100\text{mA}$		30	60	mV
Output voltage temperature coefficient	$\Delta V_O / \Delta T$	$T_j = -20 \sim +75^\circ\text{C}$ , $V_{IN} = V_O + 1\text{V}$ , $I_O = 30\text{mA}$		100		ppm/ $^\circ\text{C}$
Ripple rejection rate	RR	$V_{IN} = V_O + 1\text{V}$ , $I_O = 30\text{mA}$ , $V_{RIPPLE} = 1V_{P-P}$ , $f = 120\text{Hz}$	50	70		dB
Output noise voltage	$V_n$	$V_{IN} = V_O + 1\text{V}$ , $f = 20 \sim 80\text{kHz}$ , $I_O = 30\text{mA}$ , $C_n = 0.01 \mu\text{F}$		35 (3V item)		$\mu\text{V}_{rms}$
$C_{CONT}$ pin current while on	$I_{CONT}$	$V_{CONT} = 1.6\text{V}$		5	15	$\mu\text{A}$
$C_{CONT}$ pin high level	H		1.6		$V_{IN} + 0.3\text{V}$	V
$C_{CONT}$ pin low level	L		-0.3		0.4	V

**Measuring Circuit**




**Characteristics (33X,33XR Series)**


• **Consumption current ( $V_{IN}=4.3V$ )**




• **Output fluctuation ( $I_O=30mA$ )**




• **I/O voltage difference ( $V_{IN}=3.1V$ )**




• **Load fluctuation ( $V_{IN}=4.3V$ )**




• **Current limit ( $V_{IN}=4.3V$ )**




• **No-load input current**



• Load step (1mA-200mA)




• Chip enable transient response



• Current limit response




Small Outline SOT-25



SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN	MAX	MIN	MAX	
A	0.035	0.057	0.90	1.45	-
A1	0.000	0.006	0.00	0.15	-
A2	0.035	0.051	0.90	1.30	-
b	0.010	0.020	0.25	0.50	-
C	0.003	0.008	0.08	0.20	-
D	0.110	0.122	2.80	3.10	-
E	0.102	0.118	2.60	3.00	-
E1	0.059	0.069	1.50	1.75	-
L	0.014	0.022	0.35	0.55	-
e	0.037ref		0.95ref		-
e1	0.075ref		1.90ref		-
r	0 <sup>0</sup>	10 <sup>0</sup>	0 <sup>0</sup>	10 <sup>0</sup>	-

**Reflow Profiles**



Profile Feature	Sn-Pb Eutectic Assembly		Pb-Free Assembly	
	Large Body Pkg. thickness ≥2.5mm or Pkg. volume ≥350mm <sup>3</sup>	Small Body Pkg. thickness <2.5mm or Pkg. volume <350mm <sup>3</sup>	Large Body Pkg. thickness ≥2.5mm or Pkg. volume ≥350mm <sup>3</sup>	Small Body Pkg. thickness ≥2.5mm or Pkg. volume ≥350mm <sup>3</sup>
Average ramp-up rate (T <sub>L</sub> to T <sub>P</sub> )	3°C/second max.		3°C/second max.	
Preheat -Temperature Min(T <sub>smin</sub> ) -Temperature Max (T <sub>smax</sub> ) -Time (min to max)(t <sub>s</sub> )	100°C 150°C 60-120 seconds		150°C 200°C 60-180 seconds	
T <sub>smax</sub> to T <sub>L</sub> -Ramp-up Rate			3°C/second max.	
Time maintained above: -Temperature (T <sub>L</sub> ) -Time (t <sub>L</sub> )	183°C 60-150 seconds		217°C 60-150 seconds	
Peak Temperature(T <sub>P</sub> )	225+0/-5°C	240+0/-5°C	245+0/-5°C	250+0/-5°C
Time within 5°C of actual Peak Temperature (t <sub>p</sub> )	10-30 seconds	10-30 seconds	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second max.		3°C/second max.	
Time 25°C to Peak Temperature	6 minutes max.		8 minutes max.	

\*All temperatures refer to topside of the package, measured on the package body surface.