


MOS Field Effect Transistor

2SK1592

■ Features

- Directly driven by Ics having a 5V power supply.
 - Has low on-state resistance.
- $R_{DS(on)}=2.5 \Omega$ MAX. @ $V_{GS}=4.0V, I_D=0.3A$
- $R_{DS(on)}=2.0 \Omega$ MAX. @ $V_{GS}=10V, I_D=0.3A$



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain to source voltage	V_{DSS}	60	V
Gate to source voltage	V_{GSS}	± 20	V
Drain current (DC)	I_D	± 500	mA
Drain current(pulse) *	I_D	± 1.0	A
Power dissipation	P_D	2.0	W
Channel temperature	T_{ch}	150	$^\circ C$
Storage temperature	T_{stg}	-55 to +150	$^\circ C$

* $PW \leq 10ms$, duty cycle $\leq 5\%$

■ Electrical Characteristics $T_a = 25^\circ C$

Parameter	Symbol	Testconditons	Min	Typ	Max	Unit
Drain cut-off current	I_{BS}^{ss}	$V_{DS}=60V, V_{GS}=0$			1.0	μA
Gate leakage current	I_{GS}^{ss}	$V_{GS}=\pm 20V, V_{DS}=0$			± 1.0	μA
Gate to source cutoff voltage	$V_{GS(off)}$	$V_{DS}=10V, I_D=1mA$	0.8	1.2	2.0	V
Forward transfer admittance	$ Y_{fs} $	$V_{DS}=10V, I_D=0.5A$	400	570		ms
Drain to source on-state resistance	$R_{DS(on)}$	$V_{GS}=4.0V, I_D=0.3A$		1.6	2.5	Ω
		$V_{GS}=10V, I_D=0.3A$		1.2	2.0	Ω
Input capacitance	C_{iss}	$V_{DS}=10V, V_{GS}=0, f=1MHz$		52		pF
Output capacitance	C_{oss}			34		pF
Reverse transfer capacitance	C_{rss}			7		pF
Turn-on delay time	$t_{d(on)}$	$I_D=0.3A, V_{GS(on)}=4V, R_L=33\Omega, V_{DD}=10V, R_G=10\Omega$		60		ns
Rise time	t_r			150		ns
Turn-off delay time	$t_{d(off)}$			150		ns
Fall time	t_f			100		ns

■ Marking

Marking	NO
---------	----