

# BCR8PM-20L

Triac

Medium Power Use

REJ03G0311-0100

Rev.1.00


Aug.20.2004

## Features

- $I_{T(RMS)}$  : 8 A
- $V_{DRM}$  : 1000 V
- $I_{FGTI}$ ,  $I_{RGTI}$ ,  $I_{RGTI\text{III}}$  : 30 mA
- Viso : 2000 V
- Insulated Type
- Planar Passivation Type
- UL Recognized : Yellow Card No. E223904  
File No. E80271

## Outline

TO-220F



1.  $T_1$  Terminal
2.  $T_2$  Terminal
3. Gate Terminal

## Applications

Washing machine, inversion operation of capacitor motor, and other general controlling devices

## Maximum Ratings

Parameter	Symbol	Voltage class		Unit
		20		
Repetitive peak off-state voltage <sup>Note1</sup>	$V_{DRM}$	1000		V
Non-repetitive peak off-state voltage <sup>Note1</sup>	$V_{DSM}$	1200		V

Parameter	Symbol	Ratings	Unit	Conditions
RMS on-state current	I <sub>T</sub> (RMS)	8	A	Commercial frequency, sine full wave 360° conduction, T <sub>c</sub> = 88°C
Surge on-state current	I <sub>TSM</sub>	80	A	60Hz sinewave 1 full cycle, peak value, non-repetitive
I <sup>2</sup> t for fusing	I <sup>2</sup> t	26	A <sup>2</sup> s	Value corresponding to 1 cycle of half wave 60Hz, surge on-state current
Peak gate power dissipation	P <sub>GM</sub>	5	W	
Average gate power dissipation	P <sub>G</sub> (AV)	0.5	W	
Peak gate voltage	V <sub>GM</sub>	10	V	
Peak gate current	I <sub>GM</sub>	2	A	
Junction temperature	T <sub>j</sub>	- 40 to +125	°C	
Storage temperature	T <sub>stg</sub>	- 40 to +125	°C	
Mass	—	2.0	g	Typical value
Isolation voltage	V <sub>iso</sub>	2000	V	T <sub>a</sub> = 25°C, AC 1 minute, T <sub>1</sub> ·T <sub>2</sub> ·G terminal to case

Notes: 1. Gate open.


## Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
Repetitive peak off-state current	I <sub>DRM</sub>	—	—	2.0	mA	T <sub>j</sub> = 125°C, V <sub>DRM</sub> applied
On-state voltage	V <sub>TM</sub>	—	—	1.6	V	T <sub>c</sub> = 25°C, I <sub>TM</sub> = 12 A, Instantaneous measurement
Gate trigger voltage <sup>Note2</sup>	I	V <sub>FGTI</sub>	—	1.5	V	T <sub>j</sub> = 25°C, V <sub>D</sub> = 6 V, R <sub>L</sub> = 6 Ω, R <sub>G</sub> = 330 Ω
	II	V <sub>RGTI</sub>	—	1.5	V	
	III	V <sub>RGTIII</sub>	—	1.5	V	
Gate trigger current <sup>Note2</sup>	I	I <sub>FGTI</sub>	—	30	mA	T <sub>j</sub> = 25°C, V <sub>D</sub> = 6 V, R <sub>L</sub> = 6 Ω, R <sub>G</sub> = 330 Ω
	II	I <sub>RGTI</sub>	—	30	mA	
	III	I <sub>RGTIII</sub>	—	30	mA	
Gate non-trigger voltage	V <sub>GD</sub>	0.2	—	—	V	T <sub>j</sub> = 125°C, V <sub>D</sub> = 1/2 V <sub>DRM</sub>
Thermal resistance	R <sub>th</sub> (j-c)	—	—	3.7	°C/W	Junction to case <sup>Note3</sup>
Critical-rate of rise of off-state commutating voltage <sup>Note4</sup>	(dv/dt)c	10	—	—	V/μs	T <sub>j</sub> = 125°C

Notes: 2. Measurement using the gate trigger characteristics measurement circuit.


3. The contact thermal resistance R<sub>th</sub> (c-f) in case of greasing is 0.5°C/W.

4. Test conditions of the critical-rate of rise of off-state commutating voltage is shown in the table below.


Test conditions	Commutating voltage and current waveforms (inductive load)
1. Junction temperature T <sub>j</sub> = 125°C 2. Rate of decay of on-state commuting current (di/dt) <sub>c</sub> = - 4.0 A/ms 3. Peak off-state voltage V <sub>D</sub> = 400 V	

## Performance Curves


Maximum On-State Characteristics




Rated Surge On-State Current




Gate Characteristics (I, II and III)




Gate Trigger Current vs. Junction Temperature




Gate Trigger Voltage vs. Junction Temperature




Maximum Transient Thermal Impedance Characteristics (Junction to case)




Maximum Transient Thermal Impedance  
Characteristics (Junction to ambient)




Maximum On-State Power Dissipation




Allowable Case Temperature vs.  
RMS On-State Current




Allowable Ambient Temperature vs.  
RMS On-State Current









Allowable Ambient Temperature vs.  
RMS On-State Current




Repetitive Peak Off-State Current vs.  
Junction Temperature







## Gate Trigger Characteristics Test Circuits



Test Procedure I






Test Procedure II



Test Procedure III

## Package Dimensions

TO-220F			
EIAJ Package Code	JEDEC Code	Mass (g) (reference value)	Lead Material
Conforms	—	2.0	Cu alloy



Symbol	Dimension in Millimeters		
	Min	Typ	Max
A			
A <sub>1</sub>			
A <sub>2</sub>			
b			
D			
E			
e			
x			
y			
y <sub>1</sub>			
ZD			
ZE			

Note 1) The dimensional figures indicate representative values unless otherwise the tolerance is specified.

## Order Code

Lead form	Standard packing	Quantity	Standard order code	Standard order code example
Straight type	Vinyl sack	100	Type name +A	BCR8PM-20LA
Lead form	Plastic Magazine (Tube)	50	Type name +A – Lead forming code	BCR8PM-20LA-A8

Note : Please confirm the specification about the shipping in detail.

## Renesas Technology Corp. Sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

Keep safety first in your circuit designs!

1. Renesas Technology Corp. puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage.
- Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of nonflammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

1. These materials are intended as a reference to assist our customers in the selection of the Renesas Technology Corp. product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Renesas Technology Corp. or a third party.
2. Renesas Technology Corp. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
3. All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Renesas Technology Corp. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Renesas Technology Corp. or an authorized Renesas Technology Corp. product distributor for the latest product information before purchasing a product listed herein.
- The information described here may contain technical inaccuracies or typographical errors.
- Renesas Technology Corp. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.
- Please also pay attention to information published by Renesas Technology Corp. by various means, including the Renesas Technology Corp. Semiconductor home page (<http://www.renesas.com>).
4. When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Renesas Technology Corp. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
5. Renesas Technology Corp. semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Renesas Technology Corp. or an authorized Renesas Technology Corp. product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
6. The prior written approval of Renesas Technology Corp. is necessary to reprint or reproduce in whole or in part these materials.
7. If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
- Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
8. Please contact Renesas Technology Corp. for further details on these materials or the products contained therein.



### RENESAS SALES OFFICES

<http://www.renesas.com>

**Renesas Technology America, Inc.**  
450 Holger Way, San Jose, CA 95134-1368, U.S.A.  
Tel: <1> (408) 382-7500 Fax: <1> (408) 382-7501

**Renesas Technology Europe Limited.**  
Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, United Kingdom  
Tel: <44> (1628) 585 100, Fax: <44> (1628) 585 900

**Renesas Technology Europe GmbH**  
Dornacher Str. 3, D-85622 Feldkirchen, Germany  
Tel: <49> (89) 380 70 0, Fax: <49> (89) 929 30 11

**Renesas Technology Hong Kong Ltd.**  
7/F., North Tower, World Finance Centre, Harbour City, Canton Road, Hong Kong  
Tel: <852> 2265-6688, Fax: <852> 2375-6836

**Renesas Technology Taiwan Co., Ltd.**  
FL 10, #99, Fu-Hsing N. Rd., Taipei, Taiwan  
Tel: <886> (2) 2715-2888, Fax: <886> (2) 2713-2999

**Renesas Technology (Shanghai) Co., Ltd.**  
26/F., Ruijin Building, No.205 Maoming Road (S), Shanghai 200020, China  
Tel: <86> (21) 6472-1001, Fax: <86> (21) 6415-2952

**Renesas Technology Singapore Pte. Ltd.**  
1, Harbour Front Avenue, #06-10, Keppel Bay Tower, Singapore 098632  
Tel: <65> 6213-0200, Fax: <65> 6278-8001