



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1431 Integrated Circuit Audio Driver

Absolute Maximum Ratings: ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}	15V
Power Dissipation, P_D	550mW
Operating Temperature Range, T_{opr}	-25° to $+75^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+125^\circ\text{C}$

Electrical Characteristics: ($T_A = 25^\circ\text{C}$, $V_{CC} = 6V$, unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current	I_{CC}	$f = 1\text{kHz}$, $V_{IN} = 0$, $Z_L = 8\text{k}\Omega$	-	1.4	2.5	mA
Open Loop Voltage Gain	G_{VO}	$f = 1\text{kHz}$, $Z_L = 8\text{k}\Omega$, $V_{IN} = 0.5\text{mV}$	56	61	-	dB
Max. Output Voltage	V_{OM}	$f = 1\text{kHz}$, THD = 10%, $Z_L = 8\text{k}\Omega$	1.1	1.8	-	mV
Total Harmonic Distortion	THD	$f = 1\text{kHz}$, $V_{OUT} = 0.5V$, $Z_L = 8\text{k}\Omega$	-	1.2	3.0	%
Input Impedance	Z_{IN}	$f = 1\text{kHz}$, $Z_L = 8\text{k}\Omega$	-	2	-	$\text{k}\Omega$

Pin Connection Diagram
 (Front View)

