


SKiiP 1092GB170-474CTV



SKiiP® 2

2-pack - integrated intelligent Power System

Power section

SKiiP 1092GB170-474CTV


Features

- SKiiP technology inside
- Low loss IGBTs
- CAL diode technology
- Integrated current sensor
- Integrated temperature sensor
- Integrated heat sink
- IEC 60721-3-3 (humidity) class 3K3/IE32 (SKiiP® 2 System)
- IEC 68T.1 (climate) 40/125/56 (SKiiP® 2 power section)

- 1) with assembly of suitable MKP capacitor per terminal (SEMIKRON type is recommended)
- 2) AC connection busbars must be connected by user, copper busbars available on request


Absolute Maximum Ratings		$T_s = 25\text{ °C}$ unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT			
V_{CES}	Operating DC link voltage	1700	V
$V_{CC}^{1)}$		1200	V
V_{GES}		± 20	V
I_C	$T_s = 25\text{ (70) °C}$	1000 (750)	A
Inverse diode			
$I_F = -I_C$	$T_s = 25\text{ (70) °C}$	1000 (750)	A
I_{FSM}	$T_j = 150\text{ °C}$, $t_p = 10\text{ ms}$; sin.	8640	A
I^2t (Diode)	Diode, $T_j = 150\text{ °C}$, 10 ms	373	kA ² s
T_j , (T_{stg})	AC, 1 min. (mainterminals to heat sink)	- 40 (- 25) ... + 150 (125)	°C
V_{isol}		4000	V

Characteristics		$T_s = 25\text{ °C}$ unless otherwise specified							
Symbol	Conditions	min.	typ.	max.	Units				
IGBT									
V_{CESat}	$I_C = 800\text{ A}$, $T_j = 25\text{ (125) °C}$		3,3 (4,3)	3,9	V				
V_{CEO}	$T_j = 25\text{ (125) °C}$		1,7 (2)	2 (2,3)	V				
r_{CE}	$T_j = 25\text{ (125) °C}$		2 (2,9)	2,4 (3,3)	mΩ				
I_{CES}	$V_{GE} = 0\text{ V}$, $V_{CE} = V_{CES}$, $T_j = 25\text{ (125) °C}$		(60)	4	mA				
$E_{on} + E_{off}$	$I_C = 800\text{ A}$, $V_{CC} = 900\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 1200\text{ V}$			690	mJ				
					1017	mJ			
$R_{CC'} + EE'$	terminal chip, $T_j = 125\text{ °C}$		0,13		mΩ				
L_{CE}	top, bottom		3,8		nH				
C_{CHC}	per phase, AC-side		3,2		nF				
Inverse diode									
$V_F = V_{EC}$	$I_F = 800\text{ A}$, $T_j = 25\text{ (125) °C}$		2,3 (2,1)	2,9	V				
V_{TO}	$T_j = 25\text{ (125) °C}$		1,3 (1)	1,6 (1,3)	V				
r_T	$T_j = 25\text{ (125) °C}$		1,3 (1,4)	1,6 (1,7)	mΩ				
E_{rr}	$I_C = 800\text{ A}$, $V_{CC} = 900\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 1200\text{ V}$			85	mJ				
					101	mJ			
Mechanical data									
M_{dc}	DC terminals, SI Units	6		8	Nm				
M_{ac}	AC terminals, SI Units	13		15	Nm				
w	SKiiP® 2 System w/o heat sink		3,5		kg				
w	heat sink		8,5		kg				
Thermal characteristics (P16 heat sink; 275m³/h); "r" reference to temperature sensor									
$R_{th(j-s)I}$	per IGBT			0,02	K/W				
$R_{th(j-s)D}$	per diode			0,067	K/W				
$R_{th(s-a)}$	per module			0,033	K/W				
Z_{th}	R_i (mK/W) (max. values)	tau _i (s)							
	1 2 3 4	1	2	3	4				
$Z_{th(j-r)I}$		2	15	2	1	0,13	0,001		
$Z_{th(j-r)D}$		7	51	8	1	0,13	0,001		
$Z_{th(r-a)}$		1,6	22	7	2,4	494	165	20	0,03



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.

SKiiP 1092GB170-474CTV



SKiiP® 2

2-pack - integrated intelligent Power System

2-pack integrated gate driver

SKiiP 1092GB170-474CTV

Gate driver features


- CMOS compatible inputs
- Wide range power supply
- Integrated circuitry to sense phase current, heat sink temperature and DC-bus voltage (option)
- Short circuit protection
- Over current protection
- Over voltage protection (option)
- Power supply protected against under voltage
- Interlock of top/bottom switch
- Isolation by transformers
- Fibre optic interface (option for GB-types only)
- IEC 68T.1 (climate) 25/85/56 (SKiiP® 2 gate driver)

Absolute Maximum Ratings			
Symbol	Conditions	Values	Units
V_{S1}	stabilized 15 V power supply	18	V
V_{S2}	unstabilized 24 V power supply	30	V
V_{iH}	input signal voltage (high)	15 + 0,3	V
dv/dt	secondary to primary side	75	kV/ μ s
V_{isolIO}	input / output (AC, r.m.s., 2s)	4000	Vac
V_{isol12}	output 1 / output 2 (AC, r.m.s., 2s)	1500	Vac
f_{max}	switching frequency	7	kHz
$T_{op} (T_{stg})$	operating / storage temperature	- 25 ... + 85	°C

Characteristics				(T _a = 25 °C)	
Symbol	Conditions	min.	typ.	max.	Units
V_{S1}	supply voltage stabilized	14,4	15	15,6	V
V_{S2}	supply voltage non stabilized	20	24	30	V
I_{S1}	$V_{S1} = 15$ V	$290+490 \cdot f/f_{max} + 1,3 \cdot (I_{AC}/A)$			mA
I_{S2}	$V_{S2} = 24$ V	$220+370 \cdot f/f_{max} + 1,0 \cdot (I_{AC}/A)$			mA
V_{iT+}	input threshold voltage (High)	11,2			V
V_{iT-}	input threshold voltage (Low)	5,4			V
R_{IN}	input resistance	10			k Ω
$t_{d(on)IO}$	input-output turn-on propagation time	1,2			μ s
$t_{d(off)IO}$	input-output turn-off propagation time	3			μ s
$t_{pERRRESET}$	error memory reset time	9			μ s
t_{TD}	top / bottom switch : interlock time	3,3			μ s
$I_{analogOUT}$	8 V corresponds to max. current of 15 V supply voltage	1000			A
$I_{Vs1outmax}$	(available when supplied with 24 V)	50			mA
I_{A0max}	output current at pin 12/14	5			mA
V_{oI}	logic low output voltage	0,6			V
V_{oH}	logic high output voltage	30			V
I_{TRIPSC}	over current trip level ($I_{analog OUT} = 10$ V)	1250			A
I_{TRIPLG}	ground fault protection				A
T_{tp}	over temperature protection	110	120		°C
U_{DCTRIP}	trip level of U _{DC} -protection ($U_{analog OUT} = 9$ V); (option)	1200			V

For electrical and thermal design support please use SEMISEL.
Access to SEMISEL is via SEMIKRON website <http://www.semikron.com>.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.



Case S 4