

# VOLTAGE CONTROLLED OSCILLATOR


## SURFACE MOUNT MODEL: MFC8192-5

**OPTIMIZED BANDWIDTH**


**810 - 920 MHz**

**FEATURES:**

- ▶ Low Phase Noise Performance
- ▶ Fast Tuning
- ▶ Ideal for PLL Applications
- ▶ Small Size, Surface Mount
- ▶ Lead Free REL-PRO® Technology



**Phase Noise**



**SPECIFICATIONS (Rev. C 11/03/08)**

|                             |                            |
|-----------------------------|----------------------------|
| Frequency                   | 810 - 920 MHz              |
| Tuning Voltage              | See table below.           |
| Bias Voltage                | +5 VDC @ 30 mA (Max.)      |
| Output Power                | +3 dBm (Min.)              |
| Tuning Sensitivity          | 28 - 40 MHz/V (Typ.)       |
| Output Impedance            | 50 Ohms (Nom.)             |
| Harmonic Suppression        | 15 dB (Typ.)               |
| Frequency Pulling           | 5 MHz (Typ. @ 1.75:1 VSWR) |
| Frequency Pushing           | 2 MHz (Typ.)               |
| Tuning Port Capacitance     | 33 pF (Typ.)               |
| Phase Noise @ 10 kHz        | -106 dBc/Hz (Typ.)         |
| Operating Temperature Range | -40 to 85 °C               |


**Guaranteed Tuning Specifications**

| Tuning Voltage ( V ) | Frequency ( MHz ) |
|----------------------|-------------------|
| 0.5                  | 810 (Max.)        |
| 5                    | 920 (Min.)        |

**Absolute Maximum Ratings**

|                              |                |
|------------------------------|----------------|
| Storage Temp. Range          | -55 to +125 °C |
| Bias Voltage                 | +5.5 V         |
| Tuning Voltage               | +10 V          |
| DC Voltage Applied to RF Out | ± 25 V         |

**Package # 278LF**



This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113  
 Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787





# VOLTAGE CONTROLLED OSCILLATOR SURFACE MOUNT MODEL: MFC8192-5

OPTIMIZED BANDWIDTH

810 - 920 MHz

PERFORMANCE PLOTS



This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113  
Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787

Copyright © 2008 Synergy Microwave Corporation  
201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361  
E-Mail: sales@synergymw.com • World Wide Web: <http://www.synergymw.com>





# VOLTAGE CONTROLLED OSCILLATOR

## SURFACE MOUNT MODEL: MFC8192-5

OPTIMIZED BANDWIDTH

810 - 920 MHz

PERFORMANCE PLOTS



This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591; 7,262,670; 7,265,642; 7,292,113  
 Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787

Copyright © 2008 Synergy Microwave Corporation  
 201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361  
 E-Mail: sales@synergymw.com • World Wide Web: http://www.synergymw.com

