


CTDD3220DF-S1K-1 Series

Fixed Input Isolated & Regulated
1W Output, Single Output



FEATURES

- Efficiency:** To 73%
- Temperature Range:** -40°C to +85°C
- Isolation:** 1KVDC
- Package:** UL94-V0
- Miscellaneous:** Single Output. No external component required. No heat sink required. Industry standard pinout. DIP package style. Small Footprint. Power Density 0.16W/cm³.
- Samples available.**

CHARACTERISTICS

- Short Circuit Protection:** 1 second
- Temperature Rise at Full Load:** 25°C Max. 15°C Typ.
- Cooling:** Free air convection
- Operating Temperature Range:** -40°C to +85°C
- Storage Temperature Range:** -55°C to +125°C
- Lead Temperature:** 300°C (1.5mm from case for 10 seconds)
- Storage Humidity Range:** ≤ 95%
- Case Material:** Plastic (UL94-V0)
- MTBF:** >3,500,000 hours
- Miscellaneous:** RoHS Compliant.

SPECIFICATIONS

Part Number	Vin Nom. (VDC)	Vin Range (VDC)	Voltage Out (VDC)	Io Max. (mA)	Io Min. (mA)	Effi. Typ. (%)
CTDD3220DF-0505-S1K-W75	5	4.75-5.25	5	150	15	69
CTDD3220DF-0509-S1K-1	5	4.75-5.25	9	110	11	70
CTDD3220DF-0512-S1K-1	5	4.75-5.25	12	83	9	71
CTDD3220DF-0515-S1K-1	5	4.75-5.25	15	67	7	72
CTDD3220DF-1205-S1K-W75	12	11.4-12.6	5	150	15	69
CTDD3220DF-1209-S1K-1	12	11.4-12.6	9	110	11	71
CTDD3220DF-1212-S1K-1	12	11.4-12.6	12	83	9	72
CTDD3220DF-1215-S1K-1	12	11.4-12.6	15	67	7	72
CTDD3220DF-2405-S1K-W75	24	22.8-25.2	5	150	15	70
CTDD3220DF-2409-S1K-1	24	22.8-25.2	9	110	11	72
CTDD3220DF-2412-S1K-1	24	22.8-25.2	12	83	9	73
CTDD3220DF-2415-S1K-1	24	22.8-25.2	15	67	7	73

ISOLATION SPECIFICATIONS

Item	Test Condition	MIN	TYP	MAX	Units
Isolation Voltage	Tested for 1 minute	1000			VDC
Isolation Resistance	Test at 500VDC	1000			MΩ


OUTPUT SPECIFICATIONS

Item	Test Condition	MIN	TYP	MAX	Units
Output Power		0.1		1	W
Line regulation	For Vin change of ±5%			0.25	%
Load regulation	10% to 100% full load			1	%
Output voltage accuracy	100% full load			±3	%
Temperature drift	100% full load			0.03	%/°C
Output ripple	20MHz Bandwidth		10	15	mVp-p
Switching frequency	Full load, nominal input		100		KHz

Note:

1. All specifications measured at TA=25°C, humidity<75%, nominal input voltage and rated output unless otherwise specified.

TYPICAL CHARACTERISTICS




01.03.07


CTDD3220DF-S1K-1 Series

Fixed Input Isolated & Regulated
1W Output, Single Output

OUTLINE DIMENSIONS & RECOMMENDED FOOTPRINT DETAILS



PIN CONNECTIONS



01.03.07