

Description

The ACE7401 is the P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other batter powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

Features

- -30V/-2.8A, $R_{DS(ON)}=115\text{m}\Omega$ @ $V_{GS}=-10\text{V}$
- -30V/-2.5A, $R_{DS(ON)}=125\text{m}\Omega$ @ $V_{GS}=-4.5\text{V}$
- -30V/-1.5A, $R_{DS(ON)}=170\text{m}\Omega$ @ $V_{GS}=-2.5\text{V}$
- -30V/-1.0A, $R_{DS(ON)}=240\text{m}\Omega$ @ $V_{GS}=-1.8\text{V}$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability

Application


- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

Absolute Maximum Ratings


Parameter	Symbol	Max	Unit
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GSS}	± 12	V
Continuous Drain Current ($T_J=150^\circ\text{C}$)	I_D	-2.8	A
		-2.1	
Pulsed Drain Current	I_{DM}	-8	A
Continuous Source Current (Diode Conduction)	I_S	-1.4	A
Power Dissipation	P_D	0.33	W
		0.21	
Operating Junction Temperature	T_J	-55/150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55/150	$^\circ\text{C}$
Thermal Resistance-Junction to Ambient	$R_{\theta JA}$	105	$^\circ\text{C}/\text{W}$

Packaging Type


SOT-23-3



Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

**Ordering information****Selection Guide**


ACE7401 XX + H







**Electrical Characteristics** $T_A=25^\circ\text{C}$, unless otherwise noted




Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{GS}=0\text{V}, I_D=-250\mu\text{A}$	-30			V
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	-0.4		-1.0	
Gate Leakage Current	I_{GSS}	$V_{DS}=0\text{V}, V_{GS}=\pm 12\text{V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24\text{V}, V_{GS}=0\text{V}$			-1	uA
		$V_{DS}=-24\text{V}, V_{GS}=0\text{V} T_J=85^\circ\text{C}$			-5	
On-State Drain Current	$I_{D(\text{ON})}$	$V_{DS}=-5\text{V}, V_{GS}=-4.5\text{V}$	-4			A
Drain-Source On-Resistance	$R_{DS(\text{ON})}$	$V_{GS}=-10\text{V}, I_D=-2.8\text{A}$		0.105	0.115	Ω
		$V_{GS}=-4.5\text{V}, I_D=-2.5\text{A}$		0.125	0.135	

		$V_{GS}=-2.5V, I_D=-1.5A$		0.155	0.170	
		$V_{GS}=-1.8V, I_D=-1.0A$		0.210	0.240	
Forward Transconductance	G_{fs}	$V_{DS}=-10V, I_D=-2.8A$		4		S
Diode Forward Voltage	V_{SD}	$I_S=-1.2A, V_{GS}=0V$		-0.8	-1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DS}=-15V, V_{GS}=-4.5V, I_D=-2.0A$		5.8		nC
Gate-Source Charge	Q_{gs}			0.8		
Gate-Drain Charge	Q_{gd}			1.5		
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$		380		pF
Output Capacitance	C_{oss}			55		
Reverse Transfer Capacitance	C_{rss}			40		
Turn-On Time	$t_{d(on)}$	$V_{DD}=-15V, R_L=15\Omega, I_D=-1.0A, V_{GEN}=-10V, R_G=3\Omega$		6		nS
	t_r			3.9		
Turn-Off Time	$t_{d(off)}$			40		
	t_f			15		

Typical Performance Characteristics








Packing Information

SOT-323



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Electronics Co., LTD. As sued herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.