



# High Performance BGA Cooling Solutions w/ maxiGRIP™ Attachment


# ATS PART # ATS-53375D-C2-R0

### **Features & Benefits**

- » High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- » maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- » Designed specifically for BGAs and other surface mount packages
- » Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock Testing and Unpackaged Drop Testing standards
- » Comes preassembled with high performance, phase changing, thermal interface material







\*Image above is for illustration purposes only.

# **Thermal Performance**

AIR VELOCITY		THERMAL RESISTANCE		
FT/MIN	M/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)	
200	1.0	10	3.8	
300	1.5	6.7		
400	2.0	5.5		
500	2.5	4.8		
600	3.0	4.3		
700	3.5	3.9		
800	4.0	3.7		

## **Product Details**

DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D	INTERFACE MATERIAL	FINISH
37.5 mm	37.5 mm	9.5 mm	37.5 mm	SAINT-GOBAIN C1100F	BLACK-ANODIZED

#### NOTES

- Dimension C = heat sink height from bottom of the base to the top of the fin field.
- ATS-53375D-C1-R0 is a substitute item available utilizing an equivalent phase change material (Chomerics T766).
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- 5) Optional maxiGRIP™ Installation/Removal Tool Set P/N: MGT375
- 6) Contact ATS to learn about custom options available.



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).