


NOTES

1. CHARACTERISTICS
 DIELECTRIC WITHSTANDING VOLTAGE : 300V rms AT SEA LEVEL.
 INSULATION RESISTANCE : 1000MΩ MIN AT 100V D. C.
 CONTACT RESISTANCE : 10mΩ MAX D. C. 1A MAX
2. RATING
 VOLTAGE RATING : 100V rms MAX AT SEA LEVEL
 CURRENT RATING : 2A MAX
3. SOLDER BUCKET SIZE : 0.5 DIA
4. A DIA : φ 6.2 (φ 5.2)
 * () SLEEVE AT FITTING
5. MARKING : PRC07 T. M. W PAT

NUMBER OF CONTACT
 (VIEW ON TERMINATION
 SIDE OF INSULATOR)



9	SLEEVE	VINYL CHLORIDE	—	1	
8	CROSS RECESSED HEAD SCREW	BRASS	NICKEL PLATED	2	
7	SLOTTED SET SCREW	STEEL	NICKEL PLATED	1	
6	STEEL BALL	STEEL	CHROMIUM PLATED	3	
5	REAR SHELL	BRASS	NICKEL PLATED	1	
4	SOCKET CONTACT	BERYLLIUM COPPER ALLOY	GOLD FLASH OVER NICKEL PLATED	1 2	
3	REAR INSULATOR	PBT RESIN	—	1	
2	FRONT INSULATOR	PBT RESIN	—	1	
1	INSERT SHELL	BRASS	NICKEL PLATED	1	

品番 ITEM	部品名 DESCRIPTION	材質 MATERIAL	処理 TREATMENT	数量 QTY	備考 REMARKS
記号 SYM	変更 REVISION	第三角法 PROJECTION 第三角法 尺度 SCALE 2 / 1 単位 UNITS mm 製図 DRAWN S. SATO DATE 11. JAN. 1999 設計 ENGR T. Waki DATE 11. JAN. 99 検図 CHK T. Waki DATE 11. JAN. 99 承認 APPD K. Yagi DATE 11. JAN. 99 仕様番号 SPEC No.			
		(T.M.W) TAJIMI ELECTRONICS CO., LTD.		PRC07-J12F	
				PRC07-1007	
				1	