


# SANYO

## Cadnica

# Cell Type N-50AAA


## Specifications




Nominal Capacity		50mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	5mA	
	Quick	15mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	4 to 6Hrs.	
Ambient Temperature	Charge	Standard	0°C to +45°C [+32°F to 113°F]
		Quick	10°C to +45°C [+50°F to 113°F]
	Discharge	-20°C to +60°C [-4°F to 140°F]	
	Storage	-30°C to +50°C [-22°F to 122°F]	
Internal Impedance (Av.) (at 50% discharge)		55.0mΩ (at 1000Hz)	
Weight		4g/0.14oz	
Dimensions(D)×(H) (with tube)		10.5 <sup>0</sup> <sub>-0.5</sub> × 15.8 <sup>0</sup> <sub>-1</sub> mm	
		0.41 <sup>0</sup> <sub>-0.02</sub> × 0.62 <sup>0</sup> <sub>-0.04</sub> inch	

### Typical Characteristics


#### Charge




#### Discharge (at high rate)




#### Charge



#### Discharge (at high rate)



#### Discharge (at low rate)



#### Temperature (Charge & Discharge)

