



Advanced Analog Circuits

Preliminary Datasheet

## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

### General Description

The AZ39150 is low dropout three-terminal regulator with a typical dropout of 375mV at 1.5A output current.

The AZ39150 provides current limit and thermal shutdown. On-chip thermal shutdown provides protection against any combination of high current and ambient temperature that would create excessive junction temperatures.

The AZ39150 is available for 3.3V and 5.0V versions now. It is available in the industry standard TO-220-3 and TO-263-3 power packages.

### Features

- Minimum Guaranteed Output Current: 1.5A
- Dropout Voltage: 375mV at  $I_{OUT}=1.5A$
- Output Accuracy: 1%
- Low Ground Current
- Internal Current Limit and Thermal Protection
- Reversed-battery and Reversed-lead Insertion Protection
- Fast Transient Response

### Applications

- LCD TV
- Set Top Box
- LCD Monitor
- SMPS Post Regulator
- Laptop, Palmtop and Notebook
- Portable Instrumentation
- USB Power Supply




Figure 1. Package Types of AZ39150



Advanced Analog Circuits

Preliminary Datasheet

## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

### Pin Configuration




Figure 2. Pin Configuration of AZ39150 (Top View)

### Pin Description

Pin Number	Pin Name	Function
1	V <sub>IN</sub>	Unregulated input.
2	GND	The ground pin. This pin and TAB are internally connected.
3	V <sub>OUT</sub>	Regulated Output.



# 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Functional Block Diagram





Figure 3. Functional Block Diagram of AZ39150

## **Ordering Information**





## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Ordering Information (Continued)

Package	Temperature Range	Part Number		Marking ID		Packing Type
		Tin Lead	Lead Free	Tin Lead	Lead Free	
TO-220-3	-40 to 125°C	AZ39150T-3.3	AZ39150T-3.3E1	AZ39150T-3.3	AZ39150T-3.3E1	Tube
		AZ39150T-5.0	AZ39150T-5.0E1	AZ39150T-5.0	AZ39150T-5.0E1	Tube
TO-263-3	-40 to 125°C	AZ39150S-3.3	AZ39150S-3.3E1	AZ39150S-3.3	AZ39150S-3.3E1	Tube
		AZ39150S-3.3TR	AZ39150S-3.3TRE1	AZ39150S-3.3	AZ39150S-3.3E1	Tape & Reel
		AZ39150S-5.0	AZ39150S-5.0E1	AZ39150S-5.0	AZ39150S-5.0E1	Tube
		AZ39150S-5.0TR	AZ39150S-5.0TRE1	AZ39150S-5.0	AZ39150S-5.0E1	Tape & Reel

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant.

## Absolute Maximum Ratings (Note 1)

Parameter	Symbol	Value	Unit
Supply Voltage	V <sub>IN</sub>	15	V
Maximum Operating Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>STG</sub>	-65 to 150	°C
Lead Temperature (Soldering, 10sec)	T <sub>LEAD</sub>	300	°C
ESD (Machine Model)		300	V

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

## Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Supply Voltage	V <sub>IN</sub>		13.2	V
Operating Junction Temperature	T <sub>J</sub>	-40	125	°C



## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Electrical Characteristics

## AZ39150-3.3V Electrical Characteristics

Operating Conditions:  $V_{IN}=4.3V$ ,  $I_{OUT}=10mA$ ,  $C_{IN}=10\mu F$ ,  $C_{OUT}=10\mu F$ ,  $T_J=25^{\circ}C$ , unless otherwise specified. The **Boldface** applies over  $-40^{\circ}C \leq T_J \leq 125^{\circ}C$ .

Parameter	Symbol	Condition		Min	Typ	Max	Unit
Output Voltage	$V_{OUT}$	$I_{OUT}=10mA$		3.27	3.3	3.33	V
		$10mA \leq I_{OUT} \leq 1.5A$ , $4.3V \leq V_{IN} \leq 8V$		<b>3.23</b>	<b>3.3</b>	<b>3.37</b>	V
Line Regulation	$V_{RLINE}$	$I_{OUT}=10mA$ , $4.3V \leq V_{IN} \leq 8V$			2	17	mV
Load Regulation	$V_{RLOAD}$	$V_{IN}=4.3V$ , $10mA \leq I_{OUT} \leq 1.5A$			6.6	<b>33</b>	mV
Output Voltage Temperature Coefficient	$\Delta V_{OUT}/\Delta T$	$I_{OUT}=10mA$			<b>66</b>	<b>330</b>	$\mu V/{\circ}C$
Dropout Voltage (Note 2)	$V_{DROP}$	$\Delta V_{OUT}=1\%$	$I_{OUT}=100mA$		80	<b>200</b>	mV
			$I_{OUT}=750mA$		260		mV
			$I_{OUT}=1.5A$		375	500	mV
Ground Current	$I_{GND}$	$I_{OUT}=750mA$ , $V_{IN}=4.3V$			4	<b>20</b>	mA
		$I_{OUT}=1.5A$ , $V_{IN}=4.3V$			17		mA
Current Limit	$I_{LIMIT}$	$V_{OUT}=0V$ (Note 3)		2.0	2.8		A
Minimum Load Current	$I_{LOAD} (\text{MIN})$				7	10	mA
Output Noise Voltage (rms)		10Hz to 100KHz, $I_{OUT}=100mA$ , $C_{OUT}=10\mu F$			400		$\mu V$

Note 2: Dropout voltage is defined as the input-to-output differential when the output voltage drops to 99% of its nominal value which is measured at  $V_{OUT}+1V$  applied to  $V_{IN}$ .

Note 3:  $V_{IN}=V_{OUT(\text{NOMINAL})}+1V$ .



## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Electrical Characteristics (Continued)

## AZ39150-5.0V Electrical Characteristics

Operating Conditions:  $V_{IN}=6V$ ,  $I_{OUT}=10mA$ ,  $C_{IN}=10\mu F$ ,  $C_{OUT}=10\mu F$ ,  $T_J=25^{\circ}C$ , unless otherwise specified. The **Boldface** applies over  $-40^{\circ}C \leq T_J \leq 125^{\circ}C$ .

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Output Voltage	$V_{OUT}$	$I_{OUT}=10mA$	4.95	5.0	5.05	V
		$10mA \leq I_{OUT} \leq 1.5A$ , $6V \leq V_{IN} \leq 8V$	<b>4.90</b>	<b>5.0</b>	<b>5.10</b>	V
Line Regulation	$V_{RLINE}$	$I_{OUT}=10mA$ , $6V \leq V_{IN} \leq 8V$		3	25	mV
Load Regulation	$V_{RLOAD}$	$V_{IN}=6V$ , $10mA \leq I_{OUT} \leq 1.5A$		10	<b>50</b>	mV
Output Voltage Temperature Coefficient	$\Delta V_{OUT}/\Delta T$	$I_{OUT}=10mA$		<b>100</b>	<b>500</b>	$\mu V/{}^{\circ}C$
Dropout Voltage (Note 2)	$V_{DROP}$	$\Delta V_{OUT}=1\%$ $I_{OUT}=100mA$		80	<b>200</b>	mV
		$I_{OUT}=750mA$		260		mV
		$I_{OUT}=1.5A$		375	500	mV
Ground Current	$I_{GND}$	$I_{OUT}=750mA$ , $V_{IN}=6V$		4	<b>20</b>	mA
		$I_{OUT}=1.5A$ , $V_{IN}=6V$		17		mA
Current Limit	$I_{LIMIT}$	$V_{OUT}=0V$ (Note 3)	2.0	2.8		A
Minimum Load Current	$I_{LOAD}$ (MIN)			7	10	mA
Output Noise Voltage (rms)		10Hz to 100KHz, $I_{OUT}=100mA$ , $C_{OUT}=10\mu F$		400		$\mu V$

Note 2: Dropout voltage is defined as the input-to-output differential when the output voltage drops to 99% of its nominal value which is measured at  $V_{OUT}+1V$  applied to  $V_{IN}$ .

Note 3:  $V_{IN}=V_{OUT(NOMINAL)}+1V$ .



## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Typical Performance Characteristics




Figure 4. Dropout Voltage vs. Output Current




Figure 5. Dropout Voltage vs. Temperature




Figure 6. Ground Current vs. Output Current




Figure 7. Ground Current vs. Supply Voltage



## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Typical Performance Characteristics (Continued)




Figure 8. Ground Current vs. Supply Voltage




Figure 9. Ground Current vs. Temperature




Figure 10. Ground Current vs. Temperature




Figure 11. Ground Current vs. Temperature



## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Typical Performance Characteristics (Continued)




Figure 12. Output Voltage vs. Temperature




Figure 13. Load Transient




Figure 14. Load Transient




Figure 15. Line Transient



Advanced Analog Circuits

Preliminary Datasheet

## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

### Typical Application




Figure 16. Typical Application of AZ39150




## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

## Mechanical Dimensions

TO-220-3

Unit: mm(inch)





Advanced Analog Circuits

Preliminary Datasheet


## 1.5A ULTRA LOW DROPOUT LINEAR REGULATOR

AZ39150

### Mechanical Dimensions (Continued)

TO-263-3

Unit: mm(inch)





BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

#### IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

---

#### MAIN SITE

##### **BCD Semiconductor Manufacturing Limited**

- Wafer Fab

##### **Shanghai SIM-BCD Semiconductor Manufacturing Limited**

800, Yi Shan Road, Shanghai 200233, China

Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

##### **BCD Semiconductor Manufacturing Limited**

- IC Design Group

##### **Advanced Analog Circuits (Shanghai) Corporation**

8F, Zone B, 900, Yi Shan Road, Shanghai 200233, China

Tel: +86-21-6495 9539, Fax: +86-21-6485 9673

---

#### REGIONAL SALES OFFICE

##### **Shenzhen Office**

##### **Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd. Shenzhen Office**

##### **Advanced Analog Circuits (Shanghai) Corporation Shenzhen Office**

Room E, 5F, Noble Center, No.1006, 3rd Fuzhong Road, Futian District, Shenzhen 518026, China

Tel: +86-755-8826 7951

Fax: +86-755-8826 7865

##### **Taiwan Office**

##### **BCD Semiconductor (Taiwan) Company Limited**

4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei,

Taiwan

Tel: +886-2-2656 2808

Fax: +886-2-2656 2806

##### **USA Office**

##### **BCD Semiconductor Corporation**

30920 Huntwood Ave, Hayward,

CA 94544, U.S.A

Tel : +1-510-324-2988

Fax: +1-510-324-2788