



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet


Product Description: SAW Filter 2441.8 MHz SMD 3.0X3.0 mm

TST Part No.: TA0223A

Customer Part No.: _____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Bob Chau *Bob Chau*

Approved by: _____ Francis Chen 

Date: _____ 10, 6, 2009

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 2441.8 MHz for Bluetooth

MODEL NO.: TA0223A

REV. NO.:3

A. MAXIMUM RATING:


1. Input Power Level: 10 dB_m
2. DC voltage: 0 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

B. ELECTRICAL CHARACTERISTICS:

Item		Min.	Typ.	Max.
Center frequency	F_c (dB)	-	2441.8	-
Insertion loss (2400~2483.5 MHz)	IL (dB)	-	2.1	5.0
Amplitude ripple (2400~2483.5 MHz)	(dB)	-	0.9	3.0
Attenuation (Reference level from 0 dB)				
D.C. ~ 1700	MHz (dB)	20.0	29.0	-
1700 ~ 2200	MHz (dB)	25.0	30.0	-
2700 ~ 3100	MHz (dB)	30.0	40.0	-
3100 ~ 4000	MHz (dB)	20.0	29.0	-
4000 ~ 5000	MHz (dB)	10.0	20.0	-
VSWR (2400~2483.5 MHz)		-	1.7	2.6
Source impedance	Z_s (Ω)	-	50	-
Load impedance	Z_L (Ω)	-	50	-


Note1. The standard definitions is in JIS C 6703

C. OUTLINE DRAWING:




- △ : Year Code (2006->6, ..., 2009->9)
- : Date Code (W01->A, W02->B, ..., W27->a, ..., W52->z)



D. MEASUREMENT CIRCUIT:



E. PCB Footprint:




F. Frequency Characteristics : Transfer function




Reflections Functions :

S11 VSWR




CH1 Markers
 1: 30.377
 2.20000 GHz
 2: 1.4734
 2.40000 GHz
 3: 1.3262
 2.48350 GHz




CH1 Markers
 1: 2.1182 Ω
 -27.028 Ω
 2.20000 GHz
 2: 35.016 Ω
 5.4863 Ω
 2.40000 GHz
 3: 65.566 Ω
 -4.6094 Ω
 2.48350 GHz

S22 VSWR




CH1 Markers
 1: 30.899
 2.20000 GHz
 2: 1.4509
 2.40000 GHz
 3: 1.2184
 2.48350 GHz




CH1 Markers
 1: 2.1310 Ω
 -28.496 Ω
 2.20000 GHz
 2: 34.471 Ω
 -1.0996 Ω
 2.40000 GHz
 3: 57.602 Ω
 -7.5156 Ω
 2.48350 GHz

G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

