

SH

2

10

AGENCY APPROVAL: NA

SPECIFICATIONS:

1. INDUCTANCE: @ 0.1Vrms, 10 KHz @ ROOM TEMP. 1-6 = 2-5 = 189.6 TO 220.4 µH (205 ± 7.5%) @ ROOM TEMP. 1-6-2-5 = 758.5 TO 881.5 µH INDUCTANCE MATCH: 1-6 = 2-5 within 6% $@-40^{\circ}C$ 1-6 = 2-5 = -6% ADDITIONAL TOLERANCE @+85°C 1-6 = 2-5 = +2% ADDITIONAL TOLERANCE


2. TURNS RATO: 1-6 : 2-5 = 1 : 1 ± 1%


TITLE


3. DC RESISTANCE: OHMS MAX 1-6 = 2-5 = 4.0


4. SRF: 1-6 = 2-5 > 2.5 MHz

5. HIPOT: 50 VAC, 60 Hz, 2 SECONDS PIN 1 TO 2










ΡN



NOTE: COPLANARITY < .004 (0.15)

	TOLERANCES UNLESS OTHERWISE SPECIFIED	INCHES / DECIMAL	.XX = ± .01	$.XXX = \pm.005$	ANGLES ± 1°
1000 Parkers Lake Road, Wayzata, MN 55391, (952) 475-1173, www.schottcorp.com		MILLIMETERS (mm)	$.XX = \pm 0.20$		

REF. PWB LAYOUT