

OPS860-HM

Socket G2 2nd Gen Intel® Core™ Open Pluggable Specification (OPS) Digital Signage Player with Intel® HM65 Chipset



- | | |
|------------------|-----------------------------|
| 1. 2.5" HDD Slot | 7. Audio (Line-out) |
| 2. USB 2.0 x 2 | 8. Audio (Mic-in) |
| 3. Ethernet | 9. Power indicator |
| 4. VGA | 10. HDD indicator |
| 5. Power switch | 11. JAE TX-25 |
| 6. Reset | 12. WiFi antenna (optional) |



Specifications

| | | |
|--------------------------------------------------|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Main System | CPU | Supports socket G2 (rPGA 988B) 2nd Generation Intel® Core™ i5/ i3 processors (Sandy Bridge) (optional) |
| | Chipset | Intel® HM65 PCH |
| | System Memory | 1 x DDR3 1333 SO-DIMM max. up to 4 GB |
| | Storage | 1 x 2.5" SATA HDD tray |
| IO | Watchdog Timer | 255 levels, 1 ~ 255 sec. |
| | 2 x USB 2.0 | |
| | 1 x 10/100/1000Mbps Ethernet | |
| | 1 x VGA | |
| | 1 x power on/off button | |
| | 1 x reset button | |
| | 1 x Audio (Line-out/ Mic-in) | |
| | 1 x DVI/HDMI (via OPS JAE interconnector) | |
| | 1 x DisplayPort (via OPS JAE interconnector) | |
| | 3 x USB 2.0 (via OPS JAE interconnector) | |
| 1 x Audio (Line-out, via OPS JAE interconnector) | | |
| 1 x UART (TX/RX via OPS JAE interconnector) | | |
| Indicator | 1 x LED for system power ON | |
| | 1 x LED for HDD active | |
| WiFi | Supports 802.11 a/b/g/n (optional) | |
| Expansion Slot | 1 x PCI Express Mini Card | |
| Dimensions | 200 mm (7.87") (W) x 119 mm (4.68") (D) x 30 mm (1.18") (H) | |
| Packing Dimensions | 270 mm (10.63") (W) x 197 mm (7.76") (D) x 70 mm (2.76") (H) | |
| Weight (net/gross) | 1 kg (2.2 lb)/1.5 kg (3.3 lb) | |
| Environmental | 0° ~ +54°C (32°F ~ 130°F) (With airflow 0.7m/s) | |

Packing

- 1 x driver CD
- 1 x HDD mylar x 1
- 1 x thermal grease (syringe 1G)
- 2 x M3 x 4 screw
- 2 x M4 x 6 screw

* All specifications and photos are subject to change without notice.
© 2013 Axiomtek Co., Ltd. All rights reserved.

Features

- Open Pluggable Specification (OPS) compliance
- Supports socket G2 (rPGA 988B) 2nd Generation Intel® Core™ i5/ i3 processors (Sandy Bridge) (optional)
- DDR3 1333 SO-DIMM max. up to 4 GB
- PCIe Mini Card
- Easy maintenance: pluggable HDD and easy-to-change DRAM
- VGA connector

Overview

Industrial Panel Computers & Monitors

Heavy-duty Fanless Touch Panel Computers

Digital Signage Solutions

Healthcare & Medical Solutions

Open Frame Panel Computers

Accessories



▲ Rear view

Optional EOS Installation

Windows® 7 Embedded

Optional OS Installation

Windows® XP, Windows® 7

Ordering Information

Standard

| | |
|--------------------------------|-------------------------------------------------------------------------------|
| OPS860-HM (P/N: E22M860101) | Intel® OPS digital signage player supports socket G2 processor (Sandy Bridge) |
|--------------------------------|-------------------------------------------------------------------------------|

Optional

| | |
|---------|-----------------------------------------------------|
| OPF320 | 31.5" full HD digital signage display |
| OPF321 | 31.5" LED backlight full HD digital signage display |
| AX93157 | OPS docking board |

* Specification and certifications are based on options and may vary.

Dimensions

