

## LRG-Series Double Pole Rocker & Paddle Switches



The double pole version of the R-Series incorporates the same sleek lines as the original Curvette, in a double pole envelope. This illuminated version features silver-plated butt-action contacts with ratings to 20A/125, 15A 250VAC and withstand peak inrush currents up to 100 amps. Clear or translucent style rocker actuators and a choice of solder lug, .250 Tab and wire lead terminations enable this switch to adapt to high current applications within the Power Supply, Appliance, Exercise Equipment and Music Equipment Industries.

### Dielectric Strength

UL/CSA: 1000V - live to dead metal parts & opposite polarity

### Electrical Life


50,000 cycles

### Mechanical Life

100,000 cycles

### Operating Temperature

-40°F to 185°F (-40°C to 85°C)



**LRGSCK611 - R S - B - B / 250N**

1 Base Part Number

2 Actuator Style  
3 Actuator Color

4 Bezel Color/Style

5 Rocker Legend

6 Lamp Voltage

### 1 BASE PART NUMBER: SERIES/CIRCUITRY/RATING<sup>1</sup>/TERMINATION

15A 250 VAC, 20A 125 VAC, 3/4 HP 125-250 VAC

Standard Base	Solder Lugs	.250 Tabs	Wire Leads
OFF-NONE ON	LRGSCK610	LRGSCK611	LRGSCK615
<b>European Base</b> (22 x 30 mm cutout)			
OFF-NONE ON (Single Pole)	LRGSEK610	LRGSEK611	LRGSEK615
<b>15A 6-24 V<sup>2</sup></b>			
<b>Standard Base</b>			
OFF-NONE ON	LRGSCK510	LRGSCK511	LRGSCK515
<b>European Base</b> (22 x 30 mm cutout)			
OFF-NONE ON (Single Pole)	LRGSEK510	LRGSEK511	LRGSEK515

### 2 ACTUATOR STYLE

R rocker (translucent) C rocker (clear)

### 3 ACTUATOR COLOR

L <sup>3</sup>	lime green
A	amber
B <sup>3,5</sup>	blue
C <sup>4</sup>	white/clear
G <sup>5</sup>	green
P	yellow
R	red (clear)
S	red
W	pale red

### 4 BEZEL COLOR<sup>1</sup>

B black W white

### 5 ROCKER LEGEND

	hot stamp
NO LEGEND	0
OFF-ON vertical	A
OFF-ON horizontal	B
I-O horizontal	D
I-O vertical	E
DUAL OFF-ON, I-O vertical	H
DUAL OFF-ON, I-O horizontal	J

### 6 LAMP VOLTAGE<sup>2</sup>

006V 6V incandescent	024V 24V incandescent
012V 12V incandescent	125N 125V neon
018V 18V incandescent	250N 250V neon

### NOTES

- Additional ratings, colors and clear style actuators are available. Consult factory.
- Incandescent lamps must specify 15A 24V rating only.
- Available with incandescent lamps only.
- Clear color provided where specified with clear style rocker.
- Available with clear style rocker only.