




N-Channel 30-V (D-S), 175°C MOSFET

175°C Rated
Maximum Junction Temperature

PRODUCT SUMMARY		
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)
30	0.013 @ $V_{GS} = 10$ V	45 ^a
	0.02 @ $V_{GS} = 4.5$ V	45 ^a


TO-220AB



Top View

SUP45N03-13L

DRAIN connected to TAB



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)			
Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 10	
Continuous Drain Current ($T_J = 175^\circ\text{C}$)	I_D	$T_C = 25^\circ\text{C}$	45 ^a
		$T_C = 125^\circ\text{C}$	34 ^a
Pulsed Drain Current	I_{DM}	100	A
Avalanche Current	I_{AR}	45	
Repetitive Avalanche Energy ^b	E_{AR}	100	mJ
Maximum Power Dissipation ^b	P_D	88 ^c	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Junction-to-Ambient	R_{thJA}	85	$^\circ\text{C/W}$
Junction-to-Case	R_{thJC}	1.7	

Notes

- a. Package limited.
- b. Duty cycle $\leq 1\%$.
- c. See SOA curve for voltage derating.
- d. When mounted on 1" square PCB (FR-4 material).

For SPICE model information via the Worldwide Web: <http://www.vishay.com/www/product/spice.htm>









MOSFET SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 250 μA	30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _{DS} = 250 μA	1		3	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 20 V			± 100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30 V, V _{GS} = 0 V			1	μA
		V _{DS} = 30 V, V _{GS} = 0 V, T _J = 125 °C			50	
		V _{DS} = 30 V, V _{GS} = 0 V, T _J = 175 °C			150	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = 5 V, V _{GS} = 10 V	45			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 45 A		0.01	0.013	Ω
		V _{GS} = 10 V, I _D = 45 A, T _J = 125 °C		0.0155	0.02	
		V _{GS} = 10 V, I _D = 45 A, T _J = 175 °C		0.02	0.026	
		V _{GS} = 4.5 V, I _D = 20 A		0.0145	0.02	
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 45 A	20			S
Dynamic^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = 25 V, f = 1 MHz		2730		pF
Output Capacitance	C _{oss}			450		
Reversen Transfer Capacitance	C _{rss}			220		
Total Gate Charge ^c	Q _g	V _{DS} = 15 V, V _{GS} = 10 V, I _D = 45 A		45	70	nC
Gate-Source Charge ^c	Q _{gs}			8.5		
Gate-Drain Charge ^c	Q _{gd}			8		
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = 15 V, R _L = 0.33 Ω I _D = 45 A, V _{GEN} = 10 V, R _G = 2.5 Ω		11	20	ns
Rise Time ^c	t _r			9	20	
Turn-Off Delay Time ^c	t _{d(off)}			38	70	
Fall Time ^c	t _f			11	20	
Source-Drain Diode Ratings and Characteristics (T_C = 25 °C)^b						
Continuous Current	I _S				45	A
Pulsed Current	I _{SM}				100	
Forward Voltage ^a	V _{SD}	I _F = 45 A, V _{GS} = 0 V		1	1.3	V
Reverse Recovery Time	t _{rr}	I _F = 45 A, di/dt = 100 A/μs		35	70	ns
Peak Reverse Recovery Current	I _{RM(REC)}			1.7		A
Reverse Recovery Charge	Q _{rr}			0.03		μC

Notes:



- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- e. Guaranteed by design, not subject to production testing.
- b. Independent of operating temperature.






TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



THERMAL RATINGS





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.