



PC card drilling dimensions
(after plating — thickness: 1.60 mm)

TIN LEAD PART NUMBER
 Plating: 4 ---> flash AU
 Plating: 6 ---> 0.76µ AU

Part number D50P24A*GX00

LEAD FREE PART NUMBER
 Plating: 4 ---> flash AU
 Plating: 6 ---> 0.76µ AU

Part number D50P24A*GX00LF

rev	ecn no	dr	date
B	-	MLE	1996/11/14
C	LS05-001	MPE	2005/03/10
D	LS06-0095	LGO	2006/06/28
E	110-0059	NG	2010-02-23

www.fciconnect.com		surface	ISO 1302	tolerance std	ISO 406 ISO 1101	projection	mm
Dr	PESSON	ANGULAR	✓	TOLERANCES UNLESS OTHERWISE SPECIFIED		size	A3
Eng	PESSON	LINEAR		0.X	±0.1	Scale	2
Chr	NIRMAL GEORGE	0.XX	±2	0.XX	±0.1	ECN	110-0059
Appr	SUDHIR VARMA	Product family	2010-02-23	D-SUB	Spec ref	-	



MALE CONNECTOR DELTA D 50-EUROPE
 straight solder,harpoon.nut

CUSTOMER sheet 1 of 1
 Rev. E

European Views