

1	2		3	4	5	6	7	8
REVISIONS								
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE						
<p>REMARK:1. NO.4 MUST WITHSTAND A 6 lbs. MIN. PUSHOUT FORCE FROM NO.1 AFTER STAKING OPERATION</p> <p>2. REMARK1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.1</p> <p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626</p> <p>2. BERYLLIUM COPPER PER QQ-C-530</p> <p>3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. GOLD PL. 50 MIN THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>5. TEFLON MIL-P-19468</p>								
5	CONTACT PIN	NOTE 2	NOTE 4	1	SMAF-MCXM1-3	DIMENSIONS ARE IN MILLIMETERS		PART NO. SMAF-MCXM1-3GT50G-50
4	INSULATOR	NOTE 5	NATURAL	1	SMAF-SMBM1-2-C	UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVED DATE 10-11-01'
3	INSULATOR	NOTE 5	NATURAL	1	SMAF-MCXM1-2-B	0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4		CHECKED DATE 10-11-01'
2	BODY	NOTE 2	NOTE 3	1	SMAM-MCXM1-5-B	SCALE 4/1		DRAWN DATE 10-11-01'
1	HOUSING	NOTE 1	NOTE 3	1	SMAF-SMBM1-1	ISSUE A		FILE NO.
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.			

**Amphenol**

TITLE SMA FEMALE TO MCX MALE ADAPTOR

DRAWING NO. KJ-SMAF-MCXM1-3GT50G-50

ITEM NO.

1 2 3 4 5 6 7 8