



## GJ965

### NPN EPITAXIAL PLANAR TRANSISTOR

#### Description

The GJ965 is designed for use as AF output amplifier and flash unit.

#### Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	6.40	6.80	G	0.50	0.70
B	5.20	5.50	H	2.20	2.40
C	6.80	7.20	J	0.45	0.55
D	2.40	3.00	K	0	0.15
E	2.30 REF.		L	0.90	1.50
F	0.70	0.90	M	5.40	5.80
S	0.60	0.90	R	0.80	1.20

#### Absolute Maximum Ratings (Ta = 25°C, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Collector to Base Voltage	VCBO	40	V
Collector to Emitter Voltage	VCEO	20	V
Emitter to Base Voltage	VEBO	7	V
Collector Current (Continuous)	IC	5	A
Collector Current (Peak PT=10mS)	ICP	8	A
Junction Temperature	Tj	+150	°C
Storage Temperature	TSTG	-55 ~ +150	°C
Total Power Dissipation	PD	2	W

#### Electrical Characteristics (Rating at Ta=25°C)






Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BVCBO	40	-	-	V	IC=100uA
BVCEO	20	-	-	V	IC=1mA
BVEBO	7	-	-	V	IE=10uA
ICBO	-	-	100	nA	VCB=60V
IEBO	-	-	100	nA	VEB=7V
*VCE(sat)	-	350	1000	mV	IC=3A, IB=100mA
*hFE1	230	-	800		VCE=2V, IC=500mA
*hFE2	150	-	-		VCE=2V, IC=2A
fT	-	150	-	MHz	VCE=6V, IE=50mA
Cob	-	-	50	pF	Vcb=20V, f=1MHz

\* Pulse Test: Pulse Width ≤ 380μs, Duty Cycle ≤ 2%

#### Classification Of hFE1

Rank	Q	R	S
Range	230 ~ 380	340 ~ 600	560 ~ 800

## Characteristics Curve



### Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

### Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.  
 TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China  
 TEL : 86-21-5895-7671 FAX : 86-21-38950165