



[Product catalog](#)

[FCI Basics+](#)

[About FCI](#)

[Latest News](#)

[Employment](#)

Interactive product catalog

RM/RC Solid Machined Size 16 Socket Contact for Trim Trio™

SEARCH BY :


→ Part number

- [Product type](#)
- [Application](#)
- [Industry standard](#)
- [Product tradename](#)
- [Cross reference](#)
- [Alphabetic list](#)
- [Application tooling](#)
- [Fiber optics](#)
- [Systems & Assemblies](#)
- [Custom products](#)
- [Product literature](#)
- [Technical library](#)

RC16M23K



Trim Trio™ Machined Contacts



Region

Asia/Pacific

Contact Type

Europe

Gender

Machined

Wire Size

Socket

Insulation Grip

16

no

Selected Features

Contact Material

High conductive copper alloy

Spring Material

Beryllium copper

Contact Plating

0.40 µm (16 µin.) gold over nickel

Current Rating

13 A

Contact Resistance

< 3 milli ohms

Contact Retention

110 N min.

Operating Voltage

750 V RMS

Other Properties

Ordering data shown is for our standard product offering. For non-standard or custom pr
contact your authorized FCI representative.

[Back](#)

t



[Product catalog](#)

[FCI Basics+](#)

[About FCI](#)

[Latest News](#)

[Employment](#)



Interactive product catalog

RM/RC Solid Machined Size 16 Pin Contact for Trim Trio™

SEARCH BY :


→ Part number

- Product type
- Application
- Industry standard
- Product tradename
- Cross reference
- Alphabetic list
- Application tooling
- Fiber optics
- Systems & Assemblies
- Custom products
- Product literature
- Technical library

RM16M23K



Trim Trio™ Machined Contacts



Region

Asia/Pacific

Europe

Contact Type

Machined

Gender

Pin

Wire Size

16

Insulation Grip

no

Selected Features

Other Properties

Contact Material

High conductive copper alloy

Spring Material

Beryllium copper

Contact Plating

0.40 µm (16 µin.) gold over nickel

Current Rating

13 A

Contact Resistance

< 3 milli ohms

Contact Retention

110 N min.

Operating Voltage

750 V RMS

Ordering data shown is for our standard product offering. For non-standard or custom product contact your authorized FCI representative.

[Back](#)

t