



**FR12B02 thru  
FR12JR02**

**V<sub>RRM</sub> = 100 V - 600 V**

**I<sub>F</sub> = 12 A**


#### Features

- High Surge Capability
- Types up to 600 V V<sub>RRM</sub>

**DO-4 Package**

#### Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



#### Maximum ratings, at T<sub>j</sub> = 25 °C, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	FR12B(R)02	FR12D(R)02	FR12G(R)02	FR12J(R)02	Unit
Repetitive peak reverse voltage	V <sub>RRM</sub>		100	200	400	600	V
RMS reverse voltage	V <sub>RMS</sub>		70	140	280	420	V
DC blocking voltage	V <sub>DC</sub>		100	200	400	600	V
Continuous forward current	I <sub>F</sub>	T <sub>j</sub> ≤ 100 °C	12	12	12	12	A
Surge non-repetitive forward current, Half Sine Wave	I <sub>F,SM</sub>	T <sub>c</sub> = 25 °C, t <sub>p</sub> = 8.3 ms	180	180	180	180	A
Operating temperature	T <sub>j</sub>		-65 to 150	-65 to 150	-65 to 150	-65 to 150	°C
Storage temperature	T <sub>stg</sub>		-65 to 175	-65 to 175	-65 to 175	-65 to 175	°C

#### Electrical characteristics, at T<sub>j</sub> = 25 °C, unless otherwise specified

Parameter	Symbol	Conditions	FR12B(R)02	FR12D(R)02	FR12G(R)02	FR12J(R)02	Unit
Diode forward voltage	V <sub>F</sub>	I <sub>F</sub> = 12 A, T <sub>j</sub> = 25 °C	1.4	1.4	1.4	1.4	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> = 100 V, T <sub>j</sub> = 25 °C	25	25	25	25	µA
<b>Recovery Time</b>							
Maximum reverse recovery time	T <sub>RR</sub>	I <sub>F</sub> =0.5 A, I <sub>R</sub> =1.0 A, I <sub>RR</sub> = 0.25 A	200	200	200	250	nS
<b>Thermal characteristics</b>							
Thermal resistance, junction - case	R <sub>thJC</sub>		2.5	2.5	2.5	2.5	°C/W





# America Semiconductor

FR12B02 thru  
FR12JR02

