

SWITCHING REGURATOR APPLICATIONS

Features


- High Voltage: $BV_{DSS}=60V(\text{Min.})$
- Low C_{rSS} : $C_{rSS}=84pF(\text{Typ.})$
- Low gate charge : $Qg=26.7nC(\text{Typ.})$
- Low $R_{DS(on)}$: $R_{DS(on)}=25m\Omega(\text{Max.})$

Ordering Information

Type NO.	Marking	Package Code
STK5006P STK5006		TO-220AB-3L

Outline Dimensions

unit : mm



Absolute maximum ratings (Tc=25°C)

Characteristic Symbol		Rating	Unit
Drain-Source voltage	V_{DSS}	60	V
Gate-Source voltage	V_{GSS}	±20	V
Continuous Drain current (Tc=25°C)	I_D 50		A
Continuous Drain current (Tc=100°C)	I_D 35.4		A
Drain Current-Pulsed ①	I_{DM} 200		A
Power Dissipation (Tc=25°C)	P_D 120		W
Single Pulsed Avalanche Energy ②	E_{AS} 490		mJ
Avalanche current ①	I_{AR} 50		A
Repetitive Avalanche Energy ①	E_{AR} 12		mJ
Junction temperature	T_J	150	°C
Storage temperature range	T_{stg}	-55~175	

Thermal Resistance

Characteristic Symbol		Typ.	Max	Units
Junction to Case	$R_{th(J-C)}$	-	1.24	°C/W
Junction to Ambient	$R_{th(J-a)}$	-	62.5	

Electrical Characteristics (Tc=25°C)

Characteristic Symbol		Test Condition	Min.	Typ.	Max.	Unit	
Drain-Source breakdown voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0$	60 -		-	V	
Gate-Threshold voltage	$V_{GS(th)}$	$I_D=250\mu A, V_{DS}=V_{GS}$	2.0 -		4.0	V	
Drain-source leakage current	I_{DSS}	$V_{DS}=60V, V_{GS}=0V$ -		-	1	μA	
Gate-source leakage	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$	- -		± 100	nA	
Drain-Source on-resistance ④	$R_{DS(on)}$	$V_{GS}=10V, I_D=25A$ -		18	22	m Ω	
Forward transfer admittance ④	g_{fs}	$V_{DS}=25V, I_D=25A$ -		22	-	S	
Input capacitance	C_{iss} -	$V_{GS}=0V, V_{DS}=25V, f=1MHz$		1289	1675	pF	
Output capacitance	C_{oss}		-	445	580		
Reverse transfer capacitance	C_{rss}		- 84		110		
Turn-on delay time	$t_{d(on)}$	$V_{DD}=30V, I_D=25A$ $R_G=25\Omega$	-	15	40	ns	
Rise time	t_r		-	105	220		
Turn-off delay time	$t_{d(off)}$		④ ⑤	-	80		180
Fall time	t_f		- 85		180		
Total gate charge	Q_g -	$V_{DS}=48V, V_{GS}=10V,$ $I_D=50A$		26.7	34	nC	
Gate-source charge	Q_{gs} -		④ ⑤		5.0		-
Gate-drain("Miller")charge Q	Q_{gd}		- 10.	2	-		

Source-Drain Diode Ratings and Characteristics (Tc=25°C)

Characteristic Symbol		Test Condition	Min	Typ	Max	Units
Continuous source current	I_S	Integral reverse diode in the MOSFET	-	-	50	A
Pulsed-source current ①	I_{SM}		- -		200	
Diode forward voltage ④	V_{SD}	$V_{GS}=0V, I_S=50A$ -		-	1.5	V
Reverse recovery time	t_{rr}	$I_S=50A$ $di_F/dt=100A/us$	-	45	-	ns
Reverse recovery charge	Q_{rr}		④	- 70		-

Note ;

- ① Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ② $L=230\mu H, I_{AS}=50A, V_{DD}=25V, R_G=25\Omega$, starting $T_J=25^\circ C$
- ③ $I_S \leq 50A, di/dt \leq 300A/us, V_{DD} \leq BV_{DSS}$, starting $T_J=25^\circ C$
- ④ Pulse Test : Pulse Width < 30 0us, Duty cycle $\leq 2\%$
- ⑤ Essentially independent of operating temperature

Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_S - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $V_{DSS} - T_J$




Fig.8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_C$




Fig. 10 Safe Operating Area




Fig. 10 Gate Charge Test Circuit & Waveform




Fig. 11 Resistive Switching Test Circuit & Waveform




Fig. 12 E_{AS} Test Circuit & Waveform





Fig. 13 Diode Reverse Recovery Time Test Circuit & Waveform



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life (atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.