


SAW Bandpass Filter F1G5B



Features

- RF bandpass filter
- High attenuation
- Usable bandwidth 30MHz
- No matching 50Ω single-ended operation
- Ceramic Surface Mounted Device (SMD) Package (3.0 mm * 3.0 mm)
- RoHS Compliant

Package Dimension – SMD 3.0 × 3.0



Dimensions shown are nominal in millimeters

Body : Al₂O₃ Ceramic

Lid : Kovar, Ni Plated

Terminations : Au plating 0.3 ~ 1.0 um, Over a 1.27 ~ 8.89 um
Ni Plating


Pin Configuration

2	Input
5	Output
1, 3, 4, 6	Case ground

Maximum Ratings

Parameter	Unit	Minimum	Typical	Maximum
Operating Temperature Range	℃	-30	25	80
Storage Temperature Range	℃	-40	25	80
Power Handling Capability	dBm	-	-	10

Electrostatics Sensitive Device (ESD)

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	F1G5B	
		Rev. Date	2011-06-22	
		Rev.	NWMF01-AS01	1/7

SAW Bandpass Filter F1G5B



Specifications

Fc = 1538.5 MHz


Terminating source impedance : 50Ω

Terminating load impedance : 50Ω

	Minimum	Typical	Maximum	Unit
Center Frequency (Fc)	-	1538.5	-	MHz
Insertion Loss (1547.5 MHz)	-	2.0	3.5	dB
Insertion Loss (In Fc +/- 15 MHz)	-	2.0	3.5	dB
Amplitude Ripple (In Fc +/- 15 MHz)	-	0.9	1.5	dBp-p
VSWR (In Fc +/- 15 MHz)	-	1.5	2.0	
Relative Attenuation				
0.3 ~ 1100 MHz	27	30	-	dB
1100 ~ 1400 MHz	27	30	-	
1740 ~ 2200 MHz	30	34	-	
Input/Output Impedance	-	50	-	Ohms

Notes :

- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	F1G5B	
		Rev. Date	2011-06-22	
		Rev.	NWMF01-AS01	2/7

SAW Bandpass Filter F1G5B



Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



Marking Configuration

- ¹⁾
I²⁾
1G5B³⁾

- 1) Pad Number 1 Index
- 2) Manufacturer name
- 3) Marking Number



* Ink or Laser Marking available

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	F1G5B	
		Rev. Date	2011-06-22	
		Rev.	NWMF01-AS01	3/7

SAW Bandpass Filter F1G5B



Typical Performance (at 25°C)





	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	FIG5B	
		Rev. Date	2011-06-22	
		Rev.	NWMMF01-AS01	4/7



SAW Bandpass Filter F1G5B



Input / Output VSWR Charts



Input / Output Smith Charts




	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	FIG5B	
		Rev. Date	2011-06-22	
		Rev.	NWMMF01-AS01	5/7

SAW Bandpass Filter F1G5B




Packing Specification

1. Reeling Quantity : 1000 pcs / reel
2. Taping Structure : The tape shall be wound around the reel in the direction shown below.



Tape Specification

1. Leader part and vacant position specification




2. Tensile strength of carrier tape

4.4N/mm width

3. Top cover tape adhesion

- 1) pull off angle : 0~15°
- 2) speed : 300mm/min
- 3) force : 20~70g




	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	F1G5B	
		Rev. Date	2011-06-22	
		Rev.	NWMF01-AS01	6/7

SAW Bandpass Filter F1G5B




Carrier Tape Dimensions [unit : mm]




A	3.40 ± 0.1
B	3.40 ± 0.1
C	7.25 ± 0.1
D	1.70 ± 0.1
E	12.00 ± 0.1
F	8.00 ± 0.1

Part Direction



Reel Dimensions [unit : mm]



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	F1G5B	
		Rev. Date	2011-06-22	
		Rev.	NWMF01-AS01	7/7