



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- BRASS PER QQ-B-613
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
- PHOSPHOR BRONZE PER QQ-B-750
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

13	COVER	NOTE 2	NOTE 3	1	CV-895X07-T
12	CONTACT PIN	NOTE 1	NOTE 6	1	B5091-6-50
11	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
10	SPRING	SK5	NOTE 4	2	B50000-6
9	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
8	GASKET	RUBBER	RED	1	GS-115/8X15
7	INSULATOR	DELTRIN	NATURAL	1	B50002-3-50
6	LOCK RING	NOTE 2	NOTE 3	1	B7700-4
5	CONTACT PIN	NOTE 5	NOTE 6	1	B5990-5
4	INSULATOR	DELTRIN	NATURAL	1	B5990-4-50
3	BODY	NOTE 1	NOTE 3	1	B5990-3
2	HOUSING	NOTE 1	NOTE 3	1	B7996-2
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED	PART NO. B5072A1-ND3G-50		
TOLERANCES	APPROVED	DATE 10-11-01'	
0.5-6 = ±0.2	CHECKED	DATE 10-11-01'	
6-30 = ±0.4	DRAWN	DATE 10-11-01'	
30-120 = ±0.6	FILE NO	DRAWING NO	
120-315 = ±1			
315-1000 = ±1.6			
1000-2000 = ±2.4			

Amphenol	
TITLE BNC MALE TO FEMALE R/A ADAPTOR	
DRAWING NO. KJ-B5072A1-ND3G-50	
ITEM NO.	