



MICRO SWITCH

FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

BZ-2RQ1-A2

ALF4500

BZ-2RQ1-A2
PAGE 1 OF 1
REPLACES

M
DRAWING NUMBER

ISSUE **9**

RELEASE NO.

CHECK

REVISIONS

A	CO17410	G C H	22 MAY 63
B	CO-73287-4	D H D	17 MAY 93
C	CO-77589	K D R	29 MAR 94
D	CO-82133		
E	CO93346	CSL	25 JUL 96
F	0015139	DLT	10 SEP 98
		TSG	23 AUG 05

FORMTEK
FO-50378

DRAWN
G C H 22 MAY 63

CHECK
A.S.D 15 JUN 63



NOTES

^{△1} MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS

^{△2} HARDWARE FURNISHED UNASSEMBLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	
OPERATING FORCE ----- 9 - 13 OZ	CONTACT ARRANGEMENT S P D T	DO NOT SCALE PRINT	
RELEASE FORCE ----- 4 OZ MIN	-L96- 15 A - 125, 250, OR 480 VAC 1/2 A - 125 VDC, 1/4 A - 250 VDC 1/8 HP - 125 VAC, 1/4 HP - 250 VAC CE EN05 EC 16A 250V ~ T85 5E4	UNLESS OTHERWISE NOTED	
DIFFERENTIAL TRAVEL ----- 0004 - .0020		DIMENSIONS ARE IN INCHES	TOLERANCES ARE:
OVERTRAVEL ----- .219 MIN		ONE PLACE (.0) ±.030	TWO PLACE (.00) ±.015
		THREE PLACE (.000) ±.005	
		ANGLES ±.005	
		WEIGHT .094 LB	