


International
IOR Rectifier

SAFEIR Series
 60EPS..

INPUT RECTIFIER DIODE



$$V_F < 1V @ 30A$$

$$I_{FSM} = 950A$$

$$V_{RRM} 800 \text{ to } 1600V$$


Description/Features

The 60EPS.. rectifier **SAFEIR** series has been optimized for very low forward voltage drop, with moderate leakage. The glass passivation technology used has reliable operation up to 150° C junction temperature. Typical applications are in input rectification and these products are designed to be used with International Rectifier Switches and Output Rectifiers which are available in identical package outlines.

Major Ratings and Characteristics

| Characteristics | 60EPS.. | Units |
|---------------------------------|-------------|-------|
| $I_{F(AV)}$ Sinusoidal waveform | 60 | A |
| V_{RRM} | 800 to 1600 | V |
| I_{FSM} | 950 | A |
| V_F @ 30A, $T_J = 25^\circ C$ | 1.0 | V |
| T_J | -40 to 150 | °C |

Package Outline



TO-247AC (Modified)

Voltage Ratings

| Part Number | V_{RRM} , maximum peak reverse voltage V | V_{RSM} , maximum non repetitive peak reverse voltage V | I_{RRM} 150°C mA |
|-------------|---|--|--------------------------|
| 60EPS08 | 800 | 900 | 1 |
| 60EPS12 | 1200 | 1300 | |
| 60EPS16 | 1600 | 1700 | |

Absolute Maximum Ratings

| Parameters | 60EPS.. | Units | Conditions |
|--|---------|---------------|--|
| $I_{F(AV)}$ Max. Average Forward Current | 60 | A | @ $T_C = 118^\circ\text{C}$, 180° conduction half sine wave |
| I_{FSM} Max. Peak One Cycle Non-Repetitive Surge Current | 950 | A | 10ms Sine pulse, rated V_{RRM} applied |
| | 1100 | | 10ms Sine pulse, no voltage reapplied |
| I^2t Max. I^2t for fusing | 4512 | A^2s | 10ms Sine pulse, rated V_{RRM} applied |
| | 6300 | | 10ms Sine pulse, no voltage reapplied |
| $I^2\sqrt{t}$ Max. $I^2\sqrt{t}$ for fusing | 63000 | $A^2\sqrt{s}$ | $t = 0.1$ to 10ms, no voltage reapplied |

Electrical Specifications

| Parameters | 60EPS.. | Units | Conditions |
|---------------------------------------|---------|-----------|---------------------------------|
| V_{FM} Max. Forward Voltage Drop | 1.07 | V | @ 60A, $T_J = 25^\circ\text{C}$ |
| r_t Forward slope resistance | 3.96 | $m\Omega$ | $T_J = 150^\circ\text{C}$ |
| $V_{F(TO)}$ Threshold voltage | 0.74 | V | |
| I_{RM} Max. Reverse Leakage Current | 0.1 | mA | $T_J = 25^\circ\text{C}$ |
| | 1.0 | | $T_J = 150^\circ\text{C}$ |

$V_R = \text{rated } V_{RRM}$

Thermal-Mechanical Specifications

| Parameters | 60EPS.. | Units | Conditions |
|---|------------|--------------------|--------------------------------------|
| T_J Max. Junction Temperature Range | -40 to 150 | $^\circ\text{C}$ | |
| T_{stg} Max. Storage Temperature Range | -40 to 150 | $^\circ\text{C}$ | |
| R_{thJC} Max. Thermal Resistance Junction to Case | 0.35 | $^\circ\text{C/W}$ | DC operation |
| R_{thJA} Max. Thermal Resistance Junction to Ambient | 40 | $^\circ\text{C/W}$ | |
| R_{thCS} Typical Thermal Resistance, Case to Heatsink | 0.2 | $^\circ\text{C/W}$ | Mounting surface, smooth and greased |
| wt Approximate Weight | 6(0.21) | g(oz.) | |
| T Mounting Torque | Min. | 6(5) | Kg-cm (lbf-in) |
| | Max. | 12(10) | |
| Case Style | TO-247AC | | JEDEC (Modified) |




Fig. 1 - Current Rating Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics





Fig. 8 - Thermal Impedance Z_{thJC} Characteristics

Outline Table



Ordering Information Table

| Device Code | | | | |
|-------------|---|---|---|----|
| 60 | E | P | S | 16 |
| ① | ② | ③ | ④ | ⑤ |

| | | | | |
|--|--|-----------|------------|------------|
| <p>1 - Current Rating</p> <p>2 - Circuit Configuration: E = Single Diode</p> <p>3 - Package: P = TO-247AC (Modified)</p> <p>4 - Type of Silicon: S = Standard Recovery Rectifier</p> <p>5 - Voltage code: Code x 100 = V_{RRM}</p> | <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>08 = 800V</td> </tr> <tr> <td>12 = 1200V</td> </tr> <tr> <td>16 = 1600V</td> </tr> </table> | 08 = 800V | 12 = 1200V | 16 = 1600V |
| 08 = 800V | | | | |
| 12 = 1200V | | | | |
| 16 = 1600V | | | | |

BASE
CATHODE

CATHODE ANODE