

Switch - FL SWITCH LM 8TX - 2832632

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ethernet Lean Managed Switch with eight 10/100 Mbps RJ45 ports

Product description

The compact lean managed switches (LM) make it possible to set up flexible and economical managed Ethernet networks in an automation environment. Its huge range of connection variants and extended temperature range of -40 °C to +70 °C enable it to perfectly cover the requirements of industrial applications. The integrated software allows networks to be redundantly set up, diagnosed and monitored using IT standard protocols.

Product Features

- Web-based management, SNMP
- Compact housing
- Comprehensive fiber optic versions
- Configuration can be stored externally
- 40°C ... +70°C ambient temperature
- Configurable alarm contact



Ethernet



Key commercial data

| | |
|----------------------|---|
| Packing unit | 1 PCE |
| GTIN |  4 046356 078382 |
| Custom tariff number | 85176200 |
| Country of origin | GERMANY |

Technical data

Note:

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|-------|-------|
| Width | 45 mm |
|-------|-------|

Switch - FL SWITCH LM 8TX - 2832632

Technical data

Dimensions

| | |
|--------|--------|
| Height | 99 mm |
| Depth | 112 mm |

Interfaces

| | |
|---------------------------|--|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 8 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Copper |
| Transmission speed | 10/100 MBit/s |
| Transmission length | 100 m (per segment) |
| Interface 5 | Serial (V.24 (RS-232)) |
| Connection method | V.24 (RS-232-C), 6-pos. MINI-DIN socket (PS/2) |

Function

| | |
|----------------------------------|--|
| Basic functions | Store-and-forward switch complies with IEEE 802.3 2, priority classes in acc. with IEEE 802.1 P TCP/IP protocol, BootP-compatible, port mirroring, integrated web server function, multicast filtering, IGMP snooping, VLAN, Rapid Spanning Tree (RSTP), DHCP server |
| Supported browsers | Internet Explorer 5.5 or higher |
| Redundancy | Rapid Spanning Tree 802.1w, Fast Ring Detection |
| Status and diagnostic indicators | Per Ethernet 2 status LEDs: LINK and status activity, 100, full duplex, supply voltage U_{S1} and U_{S2} (redundant supply voltage) |

Network expansion parameters

| | |
|--|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length ((twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 18.5 V DC ... 30.5 V DC |
| Typical current consumption | 250 mA (at $U_S = 24$ V DC) |

General

| | |
|---|------------------|
| Mounting type | DIN rail |
| Type AX | Block design |
| Weight | 230 g |
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

Switch - FL SWITCH LM 8TX - 2832632

Technical data

General

| | |
|--|---|
| Permissible humidity (operation) | 30 % ... 95 % (no condensation) |
| Permissible humidity (storage/transport) | 30 % ... 95 % (no condensation) |
| Air pressure (operation) | 80 kPa ... 108 kPa (2000 above sea level) |
| Air pressure (storage/transport) | 70 kPa ... 108 kPa (3000 above sea level) |
| Noise emission | EN 61000-6-3/-4 |
| Noise immunity | EN 61000-6-2:2005 |

Mechanical tests

| | |
|--------------|--|
| Type of test | Vibration resistance in acc. with EN 60068-2-6/IEC 60068-2-6 |
| Test result | Operation/Storage/Transport: 5 g, 150 Hz, Criterion 3 |

Conformity with EMC directives

| | |
|---------------------------------|--|
| Developed in acc. with standard | IEC 61000-6.2 |
| Test standard | IEC 61000-4-2 (ESD) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-3 (immunity to radiated interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-4 (burst) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-5 (surge) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |
| Test result | Criterion A |
| Test standard | EN 60068-2-30 |

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |

UNSPSC

| | |
|--------------|----------|
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43201410 |
| UNSPSC 6.01 | 43172015 |

Switch - FL SWITCH LM 8TX - 2832632

Classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 7.0901 | 43201404 |
|---------------|----------|

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 27250501 |
| eCl@ss 5.1 | 27250501 |
| eCl@ss 6.0 | 19170106 |
| eCl@ss 7.0 | 19170106 |

Approvals

Approvals

Approvals

GL / BV / DNV / GL-SW / BSH / GL / BV / DNV / GL-SW / BSH / UL Listed / cUL Listed / GL / cULus Listed

Ex Approvals

Approvals submitted

Approval details

GL

BV

DNV

GL-SW

BSH

GL

Switch - FL SWITCH LM 8TX - 2832632

Approvals


BV

DNV


GL-SW

BSH

UL Listed 

cUL Listed 

GL

cULus Listed 

Accessories

Accessories

Assembly

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

Cable/conductor

Switch - FL SWITCH LM 8TX - 2832632

Accessories

Connecting cable - PRG CAB MINI DIN - 2730611



Connecting cable, for connecting the controller to a PC (RS-232) for PC Worx, 3 m in length

Patch cable - FL CAT5 PATCH 0,3 - 2832250



Patch cable, CAT5, assembled, 0.3 m

Patch cable - FL CAT5 PATCH 0,5 - 2832263



Patch cable, CAT5, assembled, 0.5 m

Patch cable - FL CAT5 PATCH 1,0 - 2832276



Patch cable, CAT5, assembled, 1.0 m

Patch cable - FL CAT5 PATCH 1,5 - 2832221



Patch cable, CAT5, assembled, 1.5 m

Switch - FL SWITCH LM 8TX - 2832632

Accessories

Patch cable - FL CAT5 PATCH 2,0 - 2832289



Patch cable, CAT5, assembled, 2.0 m

Patch cable - FL CAT5 PATCH 3,0 - 2832292



Patch cable, CAT5, assembled, 3.0 m

Patch cable - FL CAT5 PATCH 5,0 - 2832580



Patch cable, CAT5, assembled, 5.0 m

Patch cable - FL CAT5 PATCH 7,5 - 2832616



Patch cable, CAT5, assembled, 7.5 m

Patch cable - FL CAT5 PATCH 10,0 - 2832629



Patch cable, CAT5, assembled, 10.0 m

Switch - FL SWITCH LM 8TX - 2832632

Accessories

Patch cable - FL CAT6 PATCH 12,5 - 2891369



Patch cable, CAT6, pre-assembled, 12.5 m

Patch cable - FL CAT6 PATCH 15,0 - 2891372



Patch cable, CAT6, pre-assembled, 15.0 m

Patch cable - FL CAT6 PATCH 20,0 - 2891576



Patch cable, CAT6, pre-assembled, 20.0 m

Plug/Adapter

RJ45 plug-in connector - FL PLUG RJ45 GR/2 - 2744856



RJ45 connector, shielded, with bend protection sleeve, 2 pieces, gray for straight cables, for assembly on site. For connections that are not crossed, it is recommended that you use the connector set with gray bend protection sleeve.

RJ45 plug-in connector - FL PLUG RJ45 GN/2 - 2744571



RJ45 connector, shielded, with bend protection sleeve, 2 pieces, green for crossed cables, for assembly on site. For connections that are crossed, it is recommended that the connector set with green bend protection sleeves is used.

Switch - FL SWITCH LM 8TX - 2832632

Accessories

Software

Software - FL SNMP OPC SERVER V3 - 2701139



SNMP-OPC server, German and English, for monitoring and configuration of SNMP-capable equipment in HMI and SCADA systems

Software - FL SNMP OPC AGENT V3 - 2701136



SNMP-OPC agent, German and English, for integrating OPC-based automation solutions in company-wide network management systems

Tools

Assembly tool - FL CRIMPTOOL - 2744869



Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site

Dust protection - FL RJ45 PROTECT CAP - 2832991



Dust protection caps for RJ45 socket

Service material - FL START-UP SUPPORT - 2701426



Startup of Phoenix Contact network components and support regarding analysis, consultation/planning or configuration/startup together with a responsible person employed by the initiator.

Switch - FL SWITCH LM 8TX - 2832632

Accessories

Service material - FL MAINTENANCE SUPPORT - 2701424



Troubleshooting in an Ethernet communication network together with a responsible person employed by the initiator.

Service material - FL TRAINING - 2701427



Training for network standards, Ethernet security or wireless with Phoenix Contact components
