

Multi DomiLEDTM

Synonymous with function and performance, the Multi DomiLEDTM series is perfectly suited for a variety of cross-industrial applications due to its small package outline, durability and superior brightness.



Features:

- > High brightness tri-color surface mount LED.
- > Each color can be individually controlled
- > 120° viewing angle.
- > Small package outline (LxWxH) of 3.2 x 3.0 x 1.7mm.
- > Qualified according to JEDEC moisture sensitivity Level 2.
- > Compatible to IR reflow soldering.
- > Environmental friendly; RoHS compliance.



Applications:

- > Signs: full color video
- > Consumer & Communication: backlighting of LCDs
- > General Lighting: architectural lighting, decorative lighting

Optical Characteristics at Tj=25°C

Part Ordering Number	Color, λ_{dom} (nm)			Luminous Intensity @ If = 20mA IV (mcd)								
	Chip #1	Chip #2	Chip #3	Chip #1			Chip #2			Chip #3		
				Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.
D6RTB-DJD-TU+WX+TU-1	Red 625nm	True Green 525nm	Blue 460nm	320.0	450.0	637.0	1400.0	1800.0	2500.0	254.0	355.0	450.0
● D6RTB-DJD-TU+UV+RS-1	Red 625nm	True Green 525nm	Blue 460nm	320.0	450.0	637.0	715.0	1012.0	1400.0	126.0	180.0	254.0

● Not for new design

NOTE:

1. Reel comes in a quantity of 1000 units per reel.
2. Luminous intensity is measured with an accuracy of $\pm 11\%$.
3. All electrical and optical data are measured at room temperature; Ta = 25°C.

Electrical Characteristics at Tj=25°C

	Vf @ If = 20mA		
	Min. (V)	Typ. (V)	Max. (V)
Red	2.00	2.10	2.60
True Green	2.80	3.10	3.50
Blue	2.80	3.10	3.50

Forward voltage, Vf is measured with an accuracy of ± 0.1 V.

Absolute Maximum Ratings

	Maximum Value	Unit
DC forward current	Red; AllInGaP=30; True Green, Blue; InGaN=25	mA
Peak pulse current; (tp $\leq 10\mu$ s, Duty cycle = 0.005)	Red ; AllInGaP=500; True Green, Blue; InGaN=200	mA
Reverse voltage	Red; AllInGaP=12; True Green, Blue; InGaN= Not Designed	V
ESD threshold (HBM)	2000	V
LED junction temperature	125	°C
Operating temperature	-40 ... +100	°C
Storage temperature	-40 ... +100	°C
Thermal resistance junction/ambient (3 chips on)		
Red, R _{th JA}	500	K/W
Blue & True Green, R _{th JA}	600	K/W

Wavelength Grouping

Color	Group	Wavelength distribution (nm)
Red	Full	620 - 630
True Green	Full	521 - 536
	A	521 - 526
	B	526 - 531
	C	531 - 536
Blue	Full	460 - 470
	A	460 - 465
	B	465 - 470

Dominant wavelength is measured with an accuracy of $\pm 1\text{nm}$.

Luminous Intensity Group at $T_j=25^\circ\text{C}$

Only one IV group is allowed for each chip within reel.

Brightness Group	Luminous Intensity IV (mcd)		
	Chip #1	Chip #2	Chip #3
T3U3R3	320.0 ... 450.0	715.0 ... 1012.0	126.0 ... 180.0
T3U3S3	320.0 ... 450.0	715.0 ... 1012.0	180.0 ... 254.0
T3V3R3	320.0 ... 450.0	1012.0 ... 1400.0	126.0 ... 180.0
T3V3S3	320.0 ... 450.0	1012.0 ... 1400.0	180.0 ... 254.0
U3U3R3	450.0 ... 637.0	715.0 ... 1012.0	126.0 ... 180.0
U3U3S3	450.0 ... 637.0	715.0 ... 1012.0	180.0 ... 254.0
U3V3R3	450.0 ... 637.0	1012.0 ... 1400.0	126.0 ... 180.0
U3V3S3	450.0 ... 637.0	1012.0 ... 1400.0	180.0 ... 254.0
T3W3T3	320.0 ... 450.0	1400.0 ... 1800.0	254.0 ... 355.0
T3W3U3	320.0 ... 450.0	1400.0 ... 1800.0	355.0 ... 450.0
T3X3T3	320.0 ... 450.0	1800.0 ... 2500.0	254.0 ... 355.0
T3X3U3	320.0 ... 450.0	1800.0 ... 2500.0	355.0 ... 450.0
U3W3T3	450.0 ... 637.0	1400.0 ... 1800.0	254.0 ... 355.0
U3W3U3	450.0 ... 637.0	1400.0 ... 1800.0	355.0 ... 450.0
U3X3T3	450.0 ... 637.0	1800.0 ... 2500.0	254.0 ... 355.0
U3X3U3	450.0 ... 637.0	1800.0 ... 2500.0	355.0 ... 450.0


Luminous intensity is measured with an accuracy of $\pm 11\%$.

Correlation Between Luminous Intensity And Luminous Flux


Color	IV Bin	Luminous Intensity (mcd)		Correlated Luminous Flux (lm)	
		Min	Max	Min	Max
Red	T3	320	450	0.80	1.13
	U3	450	637	1.13	1.59
True Green	U3	715	1012	1.79	2.53
	V3	1012	1400	2.53	3.50
	W3	1400	1800	3.50	4.50
	X3	1800	2500	4.50	6.25
Blue	R3	126	180	0.32	0.45
	S3	180	254	0.45	0.64
	T3	254	355	0.64	0.89
	U3	355	450	0.89	1.13

Dominant wavelength is measured with an accuracy of $\pm 1\text{nm}$.


Relative Intensity Vs Forward Current (Red)




Relative Intensity Vs Forward Current (Blue and True Green)




Forward Current Vs Forward Voltage (Red)




Forward Current Vs Forward Voltage (Blue and True Green)




Wavelength Shift Vs Forward Current (Blue)




Wavelength Shift Vs Forward Current (True Green)




Relative Intensity vs Wavelength




Maximum Permissible Forward Current




Allowable Forward Current vs Duty Ratio



Radiation Pattern



Multi DomiLED™ : D6RTB-DJD Package Outlines




Materials

Materials	
Lead Frame	Copper alloy
Housing	High temperature resistant plastic, PPA
Encapsulant	Silicone resin
Lead-finishing	Pure tin plating, Sn


Note: Package is Pb-free.

Recommended Solder Pad




Taping and orientation


- Reels come in quantity of 1000 units.
- Reel diameter is 180 mm.



Packaging Specification




Packaging Specification



Average 1pc Multi DomiLED **1 completed bag (1000pcs)**


Weight (gram)	0.034	240 ± 10
----------------------	--------------	-----------------



For Multi DomiLED™

Cardboard Box Size	Dimensions (mm)	Empty Box Weight (kg)	Reel / Box
Super Small	325 x 225 x 190	0.38	7 reels MAX
Small	325 x 225 x 280	0.54	11 reels MAX
Medium	570 x 440 x 230	1.46	48 reels MAX
Large	570 x 440 x 460	1.92	96 reels MAX

Recommended Pb-free Soldering Profile



Revision History

Page	Subjects	Date of Modification
-	Change to official format	05 Mar 2007
3, 5	- Add Thermal Resistance Junction/Ambient - Add Max permissible Forward Current Graph - Add Allowable Forward Current Vs Duty Ratio	16 May 2007
-	Update company name	04 May 2010
2	Typo error on Optical Characteristics	05 Oct 2011
2	Not for new design: D6RTB-DJD-TU+UV+RS-1 Add new partno: D6RTB-DJD-TU+WX+TU-1	07 Jun 2012
2	Update Electrical Characteristics for True Green and Blue	16 Dec 2013
7, 9, 11	Update Packaging Outline Update Carrier Tape Update Packaging Specification	15 Mar 2016

NOTE

All the information contained in this document is considered to be reliable at the time of publishing. However, DOMINANT Opto Technologies does not assume any liability arising out of the application or use of any product described herein.

DOMINANT Opto Technologies reserves the right to make changes to any products in order to improve reliability, function or design.

DOMINANT Opto Technologies products are not authorized for use as critical components in life support devices or systems without the express written approval from the Managing Director of DOMINANT Opto Technologies.

About Us

DOMINANT Opto Technologies is a dynamic Malaysian Corporation that is among the world's leading SMT LED Manufacturers. An excellence – driven organization, it offers a comprehensive product range for diverse industries and applications. Featuring an internationally certified quality assurance acclaim, DOMINANT's extra bright LEDs are perfectly suited for various lighting applications in the automotive, consumer and communications as well as industrial sectors. With extensive industry experience and relentless pursuit of innovation, DOMINANT's state-of-art manufacturing, research and testing capabilities have become a trusted and reliable brand across the globe. More information about DOMINANT Opto Technologies can be found on the Internet at <http://www.dominant-semi.com>.

Please contact us for more information:

DOMINANT Opto Technologies Sdn. Bhd.
Lot 6, Batu Berendam, FTZ Phase III, 75350 Melaka, Malaysia
Tel: (606) 283 3566 Fax: (606) 283 0566
E-mail: sales@dominant-semi.com

