



Sales Region	Worldwide	
Series	KWS-A	
Status	Production	
Feature		
Option		
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	83% Typ.	
Rated Output Voltage[DC]	12V	
Output Voltage Range[DC]	Fixed	
Maximum Output Current	1.3A	
Maximum Output Power	15.6W	

Cases Shape & Size		
Case'] shape	On board/Power module	
Width(W)	25.4mm Nom.	
Height(H)	24mm Nom.	
Depth(D)	50.8mm Nom.	
Weight	60g Typ.	

Other		
Operating Temp. Range	-10 to 85°C	
Cooling	Convection cooling	
	UL60950-1	
Safety Standard(Certified)	CSA C22.2 No.60950-1	
	EN60950-1	
Safety Standard(Conformed)	Den-an Appendix 12	
Remarks	This page only shows representative characteristics. Please refer to the	
10111d1KS	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.